

屋内照明器具特性

品番 (品名)	XS Z B 1 0 2 1 7	
光源	LLD2401VCB1 ×1	500.0 l m
管理番号	K0193060 (0) DB 1	
B Z 分類	B Z 6	

器具効率	82 %	天井	80 %				70 %				50 %				30 %				0 %		
	上方光束		25 %	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
	下方光束		57 %	壁	10 %				10 %				10 %				10 %				0 %
室指数	照明率 (X0.01)																				Z C M
保守率	良	0.63	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6
	中	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6
	否	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56
	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56
下方投影面積	c m ²		1.25	58	50	43	38	55	47	41	37	49	42	38	34	43	38	34	31	26	23
	等価発光面積	c m ²		1.5	61	53	47	42	58	51	45	41	51	46	41	37	46	41	37	34	28
取付高さ		器具間隔最大限		2.0	66	59	53	48	62	56	51	46	55	50	46	43	49	45	42	39	32
	H m	横方向 (A)	縦方向 (B)	2.5	68	62	57	53	65	59	55	51	58	54	50	46	52	48	45	42	35
0.94 H m		0.94 H m	3.0	71	65	60	56	67	62	58	54	60	56	52	49	53	50	47	45	38	38
			4.0	73	69	65	61	70	65	62	59	62	59	56	54	56	53	51	49	41	41
			5.0	75	71	68	64	71	68	65	62	64	61	59	56	57	55	53	51	43	43
			7.0	77	74	71	69	73	71	68	66	66	64	62	60	59	58	56	54	46	46
			10.0	79	76	74	72	75	73	71	69	68	66	65	63	61	60	58	57	48	48

