

屋内照明器具特性

品番 (品名)	XS Z B 1 0 2 2 9									
光源	LLD2401VCB1 ×1					500.0 l m				
管理番号	K0193687 (0) DB 1									
B Z 分類	B Z 4 / 0 . 7 / B Z 3 / 0 . 9 / B Z 4 / 6 . 0 / B Z 5									

器具効率	89 %	天井	80 %				70 %				50 %				30 %				0 %	
	上方光束		11 %	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10
下方光束	78 %	床	10 %				10 %				10 %				10 %				0 %	
室指数			照明率 (X 0 . 0 1)																Z C M	
保守率	良	0.63	0.6	5.3	4.3	3.7	3.3	5.1	4.2	3.6	3.2	4.8	4.1	3.5	3.2	4.5	3.9	3.4	3.1	2.8
	中	0.6	0.8	6.1	5.2	4.6	4.1	5.9	5.1	4.5	4.1	5.6	4.9	4.4	4.0	5.3	4.7	4.2	3.9	3.6
	否	0.56	1.0	6.7	5.8	5.2	4.8	6.5	5.7	5.1	4.7	6.1	5.4	4.9	4.6	5.7	5.2	4.8	4.4	4.1
			1.25	7.1	6.4	5.8	5.3	6.9	6.2	5.7	5.3	6.5	5.9	5.5	5.1	6.1	5.6	5.3	4.9	4.6
下方投影面積		c m ²	1.5	7.5	6.8	6.2	5.8	7.2	6.6	6.1	5.7	6.8	6.3	5.8	5.5	6.4	6.0	5.6	5.3	4.9
等価発光面積		c m ²	2.0	7.9	7.3	6.8	6.4	7.7	7.1	6.7	6.3	7.2	6.8	6.4	6.1	6.8	6.4	6.1	5.9	5.4
取付高さ	器具間隔最大限		2.5	8.2	7.6	7.2	6.8	7.9	7.5	7.1	6.7	7.5	7.1	6.8	6.5	7.0	6.7	6.5	6.2	5.8
	横方向 (A)	縦方向 (B)	3.0	8.3	7.9	7.5	7.2	8.1	7.7	7.3	7.0	7.7	7.3	7.0	6.8	7.2	7.0	6.7	6.5	6.0
H m	1.05 H m	0.49 H m	4.0	8.6	8.2	7.9	7.6	8.3	8.0	7.7	7.5	7.9	7.6	7.4	7.2	7.5	7.2	7.0	6.9	6.4
			5.0	8.7	8.4	8.2	7.9	8.5	8.2	8.0	7.7	8.0	7.8	7.6	7.4	7.6	7.4	7.3	7.1	6.6
			7.0	8.9	8.7	8.5	8.3	8.7	8.5	8.3	8.1	8.2	8.0	7.9	7.7	7.8	7.6	7.5	7.4	6.9
			10.0	9.0	8.9	8.7	8.6	8.8	8.7	8.5	8.4	8.4	8.2	8.1	8.0	7.9	7.8	7.7	7.6	7.1

