

# 屋内照明器具特性

品番 (品名)	XY2898K																
光源	LDA4L-H-E17/E/S/W/2 ×1 440.0 lm																
管理番号	K0176849(3)DR1																
BZ分類	BZ10																

器具効率	35%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	14%	反射率	10%				10%				10%				10%				0%	
下方光束	21%		床	10%				10%				10%				10%				0%
室指数			照明率 (X0.01) ZCM																	
保守率	良	0.63	0.6	1.4	1.0	0.7	0.4	1.3	0.9	0.6	0.4	1.1	0.7	0.5	0.3	0.9	0.6	0.4	0.3	0.1
	中	0.6	0.8	1.7	1.2	0.9	0.7	1.6	1.1	0.8	0.6	1.3	1.0	0.7	0.5	1.1	0.8	0.6	0.4	0.2
	否	0.56	1.0	1.9	1.5	1.1	0.9	1.8	1.3	1.0	0.8	1.5	1.1	0.9	0.7	1.2	0.9	0.7	0.5	0.3
			1.25	2.1	1.7	1.3	1.1	1.9	1.5	1.2	1.0	1.6	1.3	1.1	0.8	1.3	1.1	0.9	0.7	0.4
下方投影面積		cm <sup>2</sup>	1.5	2.3	1.8	1.5	1.3	2.1	1.7	1.4	1.2	1.7	1.4	1.2	1.0	1.4	1.2	1.0	0.8	0.5
等価発光面積		cm <sup>2</sup>	2.0	2.5	2.1	1.8	1.6	2.3	2.0	1.7	1.4	1.9	1.7	1.4	1.2	1.6	1.4	1.2	1.0	0.7
取付高さ	器具間隔最大限		2.5	2.6	2.3	2.0	1.8	2.4	2.1	1.9	1.7	2.1	1.8	1.6	1.4	1.7	1.5	1.4	1.2	0.8
	横方向 (A)	縦方向 (B)	3.0	2.7	2.4	2.2	1.9	2.5	2.3	2.0	1.8	2.2	1.9	1.7	1.6	1.8	1.6	1.5	1.3	1.0
Hm	0.00Hm	0.00Hm	4.0	2.9	2.6	2.4	2.2	2.7	2.4	2.2	2.0	2.3	2.1	1.9	1.8	1.9	1.8	1.7	1.5	1.1
			5.0	2.9	2.7	2.5	2.3	2.8	2.6	2.4	2.2	2.4	2.2	2.1	1.9	2.0	1.9	1.8	1.7	1.2
			7.0	3.1	2.9	2.7	2.6	2.9	2.7	2.6	2.4	2.5	2.4	2.2	2.1	2.1	2.0	1.9	1.8	1.4
			10.0	3.2	3.0	2.9	2.8	3.0	2.8	2.7	2.6	2.6	2.5	2.4	2.3	2.2	2.1	2.1	2.0	1.5

