

屋内照明器具特性	
品番 (品名)	XNW1 0 3 0 B N
光源	LED5000_85_705 ×1 705.0 l m
管理番号	K0167856 (0) DB 1
BZ分類	BZ1

器具効率		1 0 0 %	反 射 率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %		
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %		
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %		
上方光束		0 %	室指数	照明率 (X 0 . 0 1) Z C M																			
下方光束		1 0 0 %																					
保守率		良	0 . 8 3	0 . 6	7 9	7 1	6 7	6 4	7 8	7 1	6 7	6 4	7 6	7 0	6 6	6 3	7 5	7 0	6 6	6 3	6 2		
		中	0 . 8 1	0 . 8	8 6	8 0	7 5	7 2	8 5	7 9	7 5	7 2	8 3	7 8	7 5	7 2	8 2	7 7	7 4	7 2	7 0		
		否	0 . 7 7	1 . 0	9 1	8 5	8 1	7 8	9 0	8 4	8 1	7 8	8 8	8 3	8 0	7 7	8 6	8 2	7 9	7 7	7 6		
				1 . 2 5	9 4	8 9	8 6	8 3	9 3	8 9	8 5	8 3	9 1	8 7	8 4	8 2	9 0	8 6	8 4	8 2	8 0		
下方投影面積		c m ²	1 . 5	9 7	9 2	8 9	8 6	9 6	9 2	8 8	8 6	9 4	9 0	8 8	8 5	9 2	8 9	8 7	8 5	8 3			
			2 . 0	1 0 0	9 6	9 3	9 1	9 8	9 5	9 3	9 0	9 6	9 4	9 1	9 0	9 5	9 2	9 0	8 9	8 7			
等価発光面積		c m ²	2 . 5	1 0 1	9 8	9 6	9 4	1 0 0	9 8	9 5	9 3	9 8	9 6	9 4	9 2	9 6	9 4	9 3	9 1	8 9			
取付高さ	器具間隔最大限		3 . 0	1 0 2	1 0 0	9 8	9 6	1 0 1	9 9	9 7	9 5	9 9	9 7	9 6	9 4	9 7	9 6	9 4	9 3	9 1			
	横方向 (A)	縦方向 (B)	4 . 0	1 0 4	1 0 2	1 0 0	9 9	1 0 3	1 0 1	9 9	9 8	1 0 1	9 9	9 8	9 7	9 9	9 7	9 6	9 5	9 3			
H m	0 . 7 2 H m	0 . 7 2 H m	5 . 0	1 0 5	1 0 3	1 0 2	1 0 0	1 0 4	1 0 2	1 0 1	1 0 0	1 0 1	1 0 0	9 9	9 8	9 9	9 8	9 7	9 7	9 4			
			7 . 0	1 0 6	1 0 4	1 0 3	1 0 2	1 0 5	1 0 3	1 0 2	1 0 2	1 0 2	1 0 1	1 0 1	1 0 0	1 0 0	1 0 0	9 9	9 8	9 6			
			1 0 . 0	1 0 6	1 0 6	1 0 5	1 0 4	1 0 5	1 0 4	1 0 4	1 0 3	1 0 3	1 0 2	1 0 2	1 0 1	1 0 1	1 0 0	1 0 0	9 9	9 7			

