

| 屋内照明器具特性 |                              |
|----------|------------------------------|
| 品番 (品名)  | XNN2051PE                    |
| 光源       | LED3000_85_1105 ×1 1105.0 lm |
| 管理番号     | K0192362 ( 0 ) DB 1          |
| BZ分類     | BZ5 / 0.7 / BZ4              |

| 器具効率     |                     | 100 %           | 反射率    | 天井   | 80 %              |     |     |     | 70 % |     |    |     | 50 % |    |    |    | 30 % |    |    |    | 0 % |
|----------|---------------------|-----------------|--------|------|-------------------|-----|-----|-----|------|-----|----|-----|------|----|----|----|------|----|----|----|-----|
|          |                     |                 |        | 壁    | 70                | 50  | 30  | 10  | 70   | 50  | 30 | 10  | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 0 % |
|          |                     |                 |        | 床    | 10 %              |     |     |     | 10 % |     |    |     | 10 % |    |    |    | 10 % |    |    |    | 0 % |
|          |                     |                 |        | 室指数  | 照明率 ( X0.01 ) ZCM |     |     |     |      |     |    |     |      |    |    |    |      |    |    |    |     |
| 保守率      |                     | 良<br>中<br>否     | 0.83   | 0.6  | 58                | 47  | 39  | 34  | 57   | 46  | 39 | 34  | 55   | 45 | 38 | 34 | 53   | 44 | 38 | 33 | 32  |
|          |                     |                 | 0.81   | 0.8  | 69                | 58  | 50  | 44  | 67   | 57  | 50 | 44  | 65   | 55 | 49 | 44 | 62   | 54 | 48 | 44 | 42  |
|          |                     |                 | 0.77   | 1.0  | 75                | 65  | 58  | 52  | 74   | 64  | 57 | 52  | 71   | 63 | 56 | 52 | 68   | 61 | 56 | 51 | 49  |
|          |                     |                 |        | 1.25 | 81                | 72  | 65  | 60  | 80   | 71  | 65 | 59  | 77   | 69 | 64 | 59 | 74   | 68 | 63 | 58 | 56  |
| 下方投影面積   |                     | cm <sup>2</sup> |        | 1.5  | 85                | 77  | 70  | 65  | 84   | 76  | 70 | 65  | 81   | 74 | 69 | 64 | 78   | 72 | 68 | 64 | 61  |
|          |                     |                 | 等価発光面積 |      | cm <sup>2</sup>   | 2.0 | 91  | 84  | 78   | 73  | 89 | 83  | 77   | 73 | 86 | 81 | 76   | 72 | 83 | 79 | 75  |
| 取付<br>高さ | 器具間隔最大限             |                 | 2.5    | 94   | 88                | 83  | 79  | 92  | 87   | 82  | 78 | 90  | 85   | 81 | 77 | 87 | 83   | 80 | 77 | 74 |     |
|          | 横方向 ( A ) 縦方向 ( B ) |                 | 3.0    | 96   | 91                | 87  | 83  | 95  | 90   | 86  | 82 | 92  | 88   | 84 | 81 | 89 | 86   | 83 | 80 | 78 |     |
| H m      | 1.23 H m            | 1.23 H m        | 4.0    | 99   | 95                | 92  | 88  | 98  | 94   | 91  | 88 | 95  | 92   | 89 | 86 | 92 | 90   | 87 | 85 | 83 |     |
|          |                     |                 | 5.0    | 101  | 98                | 95  | 92  | 100 | 97   | 94  | 91 | 97  | 94   | 92 | 90 | 94 | 92   | 90 | 88 | 86 |     |
|          |                     |                 | 7.0    | 103  | 101               | 98  | 96  | 102 | 99   | 97  | 95 | 99  | 97   | 95 | 94 | 97 | 95   | 94 | 92 | 89 |     |
|          |                     |                 | 10.0   | 105  | 103               | 101 | 100 | 103 | 102  | 100 | 99 | 101 | 99   | 98 | 97 | 98 | 97   | 96 | 95 | 92 |     |

