

屋内照明器具特性	
品番 (品名)	XNW7 5 9 0 WL
光源	LED3000_85_6805 x1 6805.0 lm
管理番号	K0164311 (2) DB 1
B Z 分類	BZ1

器具効率		1 0 0 %	反 射 率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %		
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %		
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %		
上方光束		0 %	室指数	照明率 (X 0 . 0 1)																			Z C M
下方光束		1 0 0 %																					
保守率		良	0 . 8 1	0 . 6	7 3	6 4	5 9	5 5	7 2	6 4	5 8	5 5	7 0	6 3	5 8	5 5	6 8	6 2	5 8	5 4	5 3		
		中	0 . 7 7	0 . 8	8 2	7 4	6 9	6 5	8 1	7 4	6 9	6 5	7 9	7 3	6 8	6 5	7 7	7 2	6 8	6 5	6 3		
		否	0 . 6 8	1 . 0	8 7	8 1	7 6	7 2	8 6	8 0	7 5	7 2	8 4	7 9	7 5	7 1	8 2	7 8	7 4	7 1	7 0		
				1 . 2 5	9 2	8 6	8 1	7 8	9 1	8 5	8 1	7 8	8 8	8 4	8 0	7 7	8 6	8 2	7 9	7 7	7 5		
下方投影面積		c m ²		1 . 5	9 5	8 9	8 5	8 2	9 3	8 9	8 5	8 2	9 1	8 7	8 4	8 1	8 9	8 6	8 3	8 1	7 9		
等価発光面積		c m ²		2 . 0	9 8	9 4	9 1	8 8	9 7	9 3	9 0	8 7	9 5	9 2	8 9	8 7	9 3	9 0	8 8	8 6	8 4		
取付 高さ	器具間隔最大限			2 . 5	1 0 0	9 7	9 4	9 2	9 9	9 6	9 3	9 1	9 7	9 4	9 2	9 0	9 5	9 3	9 1	8 9	8 7		
	横方向 (A)		縦方向 (B)	3 . 0	1 0 2	9 9	9 6	9 4	1 0 1	9 8	9 6	9 3	9 8	9 6	9 4	9 2	9 6	9 4	9 3	9 1	8 9		
H m	0 . 7 4 H m		0 . 7 4 H m	4 . 0	1 0 4	1 0 1	9 9	9 7	1 0 2	1 0 0	9 8	9 7	1 0 0	9 8	9 7	9 5	9 8	9 7	9 5	9 4	9 2		
				5 . 0	1 0 5	1 0 3	1 0 1	9 9	1 0 3	1 0 2	1 0 0	9 9	1 0 1	1 0 0	9 8	9 7	9 9	9 8	9 7	9 6	9 3		
				7 . 0	1 0 6	1 0 4	1 0 3	1 0 2	1 0 5	1 0 3	1 0 2	1 0 1	1 0 2	1 0 1	1 0 0	9 9	1 0 0	9 9	9 8	9 8	9 5		
				1 0 . 0	1 0 7	1 0 6	1 0 5	1 0 4	1 0 5	1 0 5	1 0 4	1 0 3	1 0 3	1 0 2	1 0 2	1 0 1	1 0 1	1 0 0	1 0 0	9 9	9 7		

