

屋内照明器具特性	
品番 (品名)	X S L G 1 0 1 V S
光源	LED3500_70_200 ×1 200.0 lm
管理番号	K0169173 (1) DR 1
B Z 分類	B Z 4

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %			
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %			
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %			
上方光束		3 0 %	室指数	照明率 (X 0 . 0 1)																		Z C M		
下方光束		7 0 %																						
保守率		良 中 否	0 . 6 3	0 . 6	0 . 6	0 . 5 6																		
			0 . 6	0 . 6	0 . 6	0 . 5 6																		
			0 . 6	0 . 6	0 . 6	0 . 5 6																		
			0 . 5 6	0 . 5 6	0 . 5 6	0 . 5 6																		
下方投影面積		c m ²	1 . 2 5	7 6	6 8	6 1	5 6	7 3	6 5	5 9	5 5	6 6	6 0	5 5	5 1	5 9	5 5	5 1	4 8	4 2				
			1 . 5	8 0	7 3	6 7	6 2	7 6	7 0	6 4	6 0	6 9	6 4	5 9	5 6	6 2	5 8	5 5	5 2	4 5				
等価発光面積		c m ²	2 . 0	8 5	7 9	7 4	6 9	8 1	7 6	7 1	6 7	7 4	6 9	6 5	6 2	6 7	6 3	6 0	5 8	5 0				
			2 . 5	8 9	8 3	7 8	7 5	8 4	8 0	7 5	7 2	7 7	7 3	7 0	6 7	6 9	6 6	6 4	6 2	5 3				
取付 高さ	器具間隔最大限		2 . 5	8 9	8 3	7 8	7 5	8 4	8 0	7 5	7 2	7 7	7 3	7 0	6 7	6 9	6 6	6 4	6 2	5 3				
	横方向 (A)	縦方向 (B)	3 . 0	9 1	8 6	8 2	7 8	8 6	8 2	7 9	7 5	7 9	7 5	7 2	7 0	7 1	6 9	6 6	6 4	5 6				
H m	1 . 1 5 H m	1 . 2 6 H m	4 . 0	9 3	9 0	8 6	8 3	8 9	8 6	8 3	8 0	8 1	7 8	7 6	7 4	7 3	7 1	7 0	6 8	5 9				
			5 . 0	9 5	9 2	8 9	8 7	9 1	8 8	8 6	8 3	8 3	8 0	7 9	7 7	7 5	7 3	7 2	7 0	6 1				
			7 . 0	9 7	9 5	9 3	9 1	9 3	9 1	8 9	8 7	8 4	8 3	8 1	8 0	7 7	7 5	7 4	7 3	6 3				
			1 0 . 0	9 8	9 7	9 5	9 4	9 4	9 3	9 1	9 0	8 6	8 5	8 4	8 3	7 8	7 7	7 6	7 5	6 5				

