

屋内照明器具特性	
品番 (品名)	XS Z B 8 3 0 1 4
光源	LLD2401LCB1 ×1                      500.0 l m
管理番号	K0193686 ( 0 ) DB 1
B Z 分類	BZ2 / 1.8 / BZ3 / 8.5 / BZ4

器具効率	93 %	天井	80 %				70 %				50 %				30 %				0 %	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
上方光束	9 %	反射率	床	10 %				10 %				10 %				10 %				0 %
下方光束	84 %		室指数	照明率 ( X0.01 )																ZCM
保守率	良 中 否 0.63 0.6 0.56	0.6	61	52	46	42	59	51	46	42	57	49	45	41	54	48	44	41	39	
		0.8	69	60	55	51	67	59	54	50	64	57	53	49	61	56	52	48	46	
		1.0	74	66	61	57	72	65	60	56	69	63	58	55	66	61	57	54	51	
		1.25	78	71	66	62	76	70	65	61	73	67	63	60	69	65	61	59	56	
下方投影面積	c m <sup>2</sup>	1.5	81	75	70	66	79	74	69	65	75	71	67	64	72	68	65	62	59	
		2.0	85	80	76	72	83	78	74	71	79	75	72	69	76	72	70	67	64	
取付高さ	器具間隔最大限		2.5	88	83	79	76	85	81	78	75	81	78	75	73	78	75	73	71	67
	横方向 ( A )	縦方向 ( B )	3.0	89	85	82	79	87	84	80	78	83	80	78	75	79	77	75	73	69
H m	0.63 H m	0.63 H m	4.0	91	88	85	83	89	86	84	81	85	83	81	79	81	79	78	76	72
			5.0	93	90	88	85	90	88	86	84	86	84	83	81	83	81	80	78	74
			7.0	94	92	90	89	92	90	88	87	88	86	85	84	84	83	82	81	76
			10.0	95	94	92	91	93	92	91	89	89	88	87	86	85	84	84	83	78

