

# 屋内照明器具特性

品番 (品名)	XS Z D 1 0 6 0 L	
光源	LLD2410LCB1 ×1	500.0 l m
管理番号	K0191449 ( 0 ) DB 1	
B Z 分類	B Z 1	

器具効率	97 %	天井	80 %				70 %				50 %				30 %				0 %	
	上方光束 0 %		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
下方光束	97 %	床		10 %				10 %				10 %				10 %				0 %
室指数	照明率 ( X 0 . 0 1 )																			Z C M
保守率	良 0.67	0.6	0.6	86	81	78	76	85	81	78	76	84	80	78	76	83	80	77	76	75
	中 0.63		0.8	91	86	83	81	90	86	83	81	89	85	83	81	87	84	82	81	80
	否 0.56		1.0	93	90	87	85	93	89	87	85	91	88	86	84	90	87	85	84	83
下方投影面積 等価発光面積	c m <sup>2</sup>	c m <sup>2</sup>	1.25	96	92	90	88	95	92	89	88	93	91	89	87	92	90	88	87	85
			1.5	97	94	92	90	96	94	91	90	95	92	91	89	93	91	90	88	87
取付高さ	器具間隔最大限		2.5	100	98	97	95	99	98	96	95	98	96	95	94	96	95	94	93	91
	横方向 ( A )	縦方向 ( B )	3.0	101	99	98	96	100	99	97	96	98	97	96	95	97	95	95	94	92
H m	0.84 H m	0.84 H m	4.0	102	101	99	98	101	100	99	98	99	98	97	96	97	96	95	93	
			5.0	103	102	101	100	102	101	100	99	100	99	98	97	98	97	97	96	94
			7.0	103	103	102	101	102	102	101	100	100	99	99	98	98	97	97	95	
			10.0	104	103	103	102	103	102	102	101	101	100	100	99	98	98	98	95	

