

屋内照明器具特性	
品番 (品名)	XSZP3005L+LGK9100W
光源	LLD3400LCB1 ×1 700.0 lm
管理番号	K0191394 (0) DB 1
BZ分類	BZ1

器具効率		77 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) ZCM																
保守率		良 中 否	0.67	0.6	55	48	44	41	55	48	44	41	53	47	44	41	52	47	43	41	40
			0.63	0.8	63	57	53	50	62	56	52	50	60	55	52	49	59	55	52	49	48
			0.56	1.0	67	62	58	55	66	61	58	55	65	61	57	55	63	60	57	55	53
				1.25	71	66	63	60	70	66	62	60	68	65	62	60	67	64	61	59	58
下方投影面積		cm ²		1.5	73	69	66	63	72	68	65	63	70	67	65	63	69	66	64	62	61
				2.0	76	73	70	68	75	72	69	67	73	71	69	67	72	69	68	66	65
等価発光面積		cm ²		2.5	77	75	72	71	77	74	72	70	75	73	71	69	73	71	70	69	67
				3.0	79	76	74	72	78	75	74	72	76	74	73	71	74	73	71	70	69
H _m	1.32 H _m	1.32 H _m		4.0	80	78	76	75	79	77	76	75	77	76	75	73	76	74	73	72	71
				5.0	81	79	78	77	80	78	77	76	78	77	76	75	76	75	75	74	72
				7.0	82	80	79	79	81	80	79	78	79	78	77	77	77	77	76	75	73
				10.0	82	81	81	80	81	81	80	79	80	79	78	78	78	77	77	77	74

