

屋内照明器具特性	
品番 (品名)	XSZR1020L
光源	L LD2420LCB1 ×1 500.0 l m
管理番号	K0192053 (0) DB 1
BZ分類	BZ1

器具効率 上方光束 下方光束	87 % 0 % 87 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
		壁	床	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
		室指数		照明率 (X0.01) ZCM																
保守率	良 0.63	0.6	0.56	0.6	69	63	59	57	69	63	59	57	62	59	57	66	62	59	56	55
	中 0.6			0.8	75	70	66	64	74	70	66	64	73	69	66	63	72	68	65	62
	否 0.56			1.0	79	74	71	68	78	74	70	68	77	73	70	68	75	72	69	66
下方投影面積 等価発光面積				1.25	82	78	75	72	81	77	74	72	79	76	74	72	78	75	73	70
				1.5	84	80	77	75	83	80	77	75	81	78	76	74	80	77	75	74
				2.0	86	83	81	79	86	83	81	79	84	81	80	78	82	80	79	77
取付高さ H m	器具間隔最大限			2.5	88	85	83	82	87	85	83	81	85	83	82	80	84	82	81	79
	横方向 (A)	縦方向 (B)		3.0	89	87	85	83	88	86	84	83	86	85	83	82	84	83	82	81
	0.55 H m	0.55 H m		4.0	90	89	87	86	89	88	86	85	87	86	85	84	86	85	84	83
				5.0	91	90	88	87	90	89	88	87	88	87	86	85	86	85	85	84
				7.0	92	91	90	89	91	90	89	88	89	88	87	87	87	87	86	85
				10.0	92	92	91	90	91	91	90	90	89	89	89	88	88	87	87	84

