

屋内照明器具特性	
品番 (品名)	XSZR1040L
光源	L LD2420LCB1 ×1 500.0 l m
管理番号	K0192053 (0) DB 1
B Z 分類	BZ1

器具効率		87 %	反 射 率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
				床	10 %				10 %				10 %				10 %				0 %	
上方光束		0 %	室指数	照明率 (X0.01)																		Z C M
下方光束		87 %																				
保守率		良 中 否	0.63	0.6	69	63	59	57	69	63	59	57	67	62	59	57	66	62	59	56	55	
			0.6	0.8	75	70	66	64	74	70	66	64	73	69	66	63	72	68	65	63	62	
			0.56	1.0	79	74	71	68	78	74	70	68	77	73	70	68	75	72	69	67	66	
			1.25	82	78	75	72	81	77	74	72	79	76	74	72	78	75	73	71	70		
下方投影面積		c m ²	1.5	84	80	77	75	83	80	77	75	81	78	76	74	80	77	75	74	72		
			2.0	86	83	81	79	86	83	81	79	84	81	80	78	82	80	79	77	76		
取付 高さ	器具間隔最大限		2.5	88	85	83	82	87	85	83	81	85	83	82	80	84	82	81	79	78		
	横方向 (A)	縦方向 (B)	3.0	89	87	85	83	88	86	84	83	86	85	83	82	84	83	82	81	79		
H m	0.55 H m	0.55 H m	4.0	90	89	87	86	89	88	86	85	87	86	85	84	86	85	84	83	81		
			5.0	91	90	88	87	90	89	88	87	88	87	86	85	86	85	85	84	82		
			7.0	92	91	90	89	91	90	89	88	89	88	87	87	87	87	86	85	83		
			10.0	92	92	91	90	91	91	90	90	89	89	89	88	88	87	87	87	84		

