

屋内照明器具特性	
品番 (品名)	XSZR1060V
光源	LLD2410VCB1 ×1 500.0 l m
管理番号	K0192052 (0) DB 1
B Z 分類	BZ1

器具効率		91 %	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
					床	10 %				10 %				10 %				10 %			
上方光束		0 %	室指数	照明率 (X0.01)																Z C M	
下方光束		91 %																			
保守率		良 中 否	0.63	0.6	71	64	60	57	70	63	59	57	68	63	59	56	67	62	59	56	55
			0.6	0.8	77	72	67	65	77	71	67	64	75	70	67	64	74	69	66	64	63
			0.56	1.0	82	76	73	70	81	76	72	70	79	75	72	69	77	74	71	69	68
				1.25	85	80	77	74	84	80	77	74	82	79	76	74	81	78	75	73	72
下方投影面積		c m ²		1.5	87	83	80	78	86	83	80	77	84	81	79	77	83	80	78	76	75
等価発光面積			c m ²	2.0	90	87	84	82	89	86	84	81	87	85	83	81	85	83	82	80	78
取付 高さ	器具間隔最大限		2.5	92	89	87	85	91	88	86	84	89	87	85	83	87	85	84	82	81	
	横方向 (A)		縦方向 (B)	3.0	93	90	88	87	92	90	88	86	90	88	86	85	88	87	85	84	82
H m	0.75 H m		0.75 H m	4.0	94	92	91	89	93	91	90	89	91	90	89	87	89	88	87	86	84
				5.0	95	93	92	91	94	93	91	90	92	91	90	89	90	89	88	88	85
				7.0	96	95	94	93	95	94	93	92	93	92	91	91	91	90	90	89	87
				10.0	97	96	95	94	95	95	94	94	93	93	92	92	92	91	91	90	88

