

| 屋内照明器具特性 |                             |
|----------|-----------------------------|
| 品番 (品名)  | XSZR3001N                   |
| 光源       | LLD3401NCB1 ×1 700.0 lm     |
| 管理番号     | K0192060 ( 0 ) DB 1         |
| BZ分類     | BZ1 / 3.5 / BZ2 / 6.0 / BZ1 |

| 器具効率             |                 | 62 %                               | 反射率  | 天井   | 80 %          |    |    |    | 70 % |    |    |    | 50 % |    |    |    | 30 % |    |    |    | 0 %  |
|------------------|-----------------|------------------------------------|------|------|---------------|----|----|----|------|----|----|----|------|----|----|----|------|----|----|----|------|
|                  |                 |                                    |      | 壁    | 70            | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 0 %  |
|                  |                 |                                    |      | 床    | 10 %          |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 0 %  |
| 上方光束<br>下方光束     |                 | 0 %<br>62 %                        |      |      | 照明率 ( X0.01 ) |    |    |    |      |    |    |    |      |    |    |    |      |    |    |    | Z CM |
| 保守率              |                 | 良<br>中<br>否                        | 0.63 | 0.6  | 44            | 39 | 35 | 33 | 44   | 39 | 35 | 33 | 43   | 38 | 35 | 33 | 42   | 38 | 35 | 33 | 32   |
|                  |                 |                                    | 0.6  | 0.8  | 50            | 45 | 42 | 39 | 49   | 45 | 42 | 39 | 48   | 44 | 41 | 39 | 47   | 44 | 41 | 39 | 38   |
|                  |                 |                                    |      | 1.0  | 54            | 49 | 46 | 44 | 53   | 49 | 46 | 44 | 52   | 48 | 45 | 43 | 50   | 47 | 45 | 43 | 42   |
|                  |                 |                                    | 0.56 | 1.25 | 56            | 53 | 50 | 48 | 56   | 52 | 49 | 47 | 54   | 51 | 49 | 47 | 53   | 50 | 48 | 47 | 46   |
| 下方投影面積<br>等価発光面積 |                 | cm <sup>2</sup><br>cm <sup>2</sup> |      | 1.5  | 58            | 55 | 52 | 50 | 57   | 54 | 52 | 50 | 56   | 53 | 51 | 50 | 55   | 53 | 51 | 49 | 48   |
|                  |                 |                                    |      | 2.0  | 61            | 58 | 56 | 54 | 60   | 57 | 55 | 53 | 58   | 56 | 54 | 53 | 57   | 55 | 54 | 52 | 51   |
| 取付<br>高さ         | 器具間隔最大限         |                                    |      | 2.5  | 62            | 60 | 58 | 56 | 61   | 59 | 57 | 56 | 60   | 58 | 56 | 55 | 58   | 57 | 56 | 55 | 53   |
|                  | 横方向 (A) 縦方向 (B) |                                    |      | 3.0  | 63            | 61 | 59 | 58 | 62   | 60 | 59 | 57 | 61   | 59 | 58 | 57 | 59   | 58 | 57 | 56 | 55   |
| H m              | 1.07 H m        | 1.07 H m                           |      | 4.0  | 64            | 63 | 61 | 60 | 63   | 62 | 61 | 59 | 62   | 61 | 60 | 59 | 61   | 60 | 59 | 58 | 56   |
|                  |                 |                                    |      | 5.0  | 65            | 63 | 62 | 61 | 64   | 63 | 62 | 61 | 63   | 62 | 61 | 60 | 61   | 60 | 60 | 59 | 57   |
|                  |                 |                                    |      | 7.0  | 66            | 65 | 64 | 63 | 65   | 64 | 63 | 62 | 63   | 63 | 62 | 61 | 62   | 61 | 61 | 60 | 59   |
|                  |                 |                                    |      | 10.0 | 66            | 65 | 65 | 64 | 65   | 65 | 64 | 64 | 64   | 63 | 63 | 62 | 63   | 62 | 62 | 61 | 60   |

