

屋内照明器具特性	
品番 (品名)	XSZR3001V
光源	LLD3401VCB1 ×1 700.0 lm
管理番号	K0192060 (0) DB 1
BZ分類	BZ1 / 3.5 / BZ2 / 6.0 / BZ1

器具効率		6 2 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
上方光束 下方光束		0 % 6 2 %	室指数	照明率 (X 0 . 0 1) Z C M																		
保守率		良 中 否	0 . 6 3	0 . 6	4 4	3 9	3 5	3 3	4 4	3 9	3 5	3 3	4 3	3 8	3 5	3 3	4 2	3 8	3 5	3 3	3 2	
			0 . 6	0 . 8	5 0	4 5	4 2	3 9	4 9	4 5	4 2	3 9	4 8	4 4	4 1	3 9	4 7	4 4	4 1	3 9	3 8	
			0 . 5 6	1 . 0	5 4	4 9	4 6	4 4	5 3	4 9	4 6	4 4	5 2	4 8	4 5	4 3	5 0	4 7	4 5	4 3	4 2	
				1 . 2 5	5 6	5 3	5 0	4 8	5 6	5 2	4 9	4 7	5 4	5 1	4 9	4 7	5 3	5 0	4 8	4 7	4 6	
下方投影面積		cm ²	1 . 5	5 8	5 5	5 2	5 0	5 7	5 4	5 2	5 0	5 6	5 3	5 1	5 0	5 5	5 3	5 1	4 9	4 8		
等価発光面積		cm ²	2 . 0	6 1	5 8	5 6	5 4	6 0	5 7	5 5	5 3	5 8	5 6	5 4	5 3	5 7	5 5	5 4	5 2	5 1		
取付 高さ	器具間隔最大限		2 . 5	6 2	6 0	5 8	5 6	6 1	5 9	5 7	5 6	6 0	5 8	5 6	5 5	5 8	5 7	5 6	5 5	5 3		
	横方向 (A) 縦方向 (B)		3 . 0	6 3	6 1	5 9	5 8	6 2	6 0	5 9	5 7	6 1	5 9	5 8	5 7	5 9	5 8	5 7	5 6	5 5		
H m	1 . 0 7 H m	1 . 0 7 H m	4 . 0	6 4	6 3	6 1	6 0	6 3	6 2	6 1	5 9	6 2	6 1	6 0	5 9	6 1	6 0	5 9	5 8	5 6		
			5 . 0	6 5	6 3	6 2	6 1	6 4	6 3	6 2	6 1	6 3	6 2	6 1	6 0	6 1	6 0	6 0	5 9	5 7		
			7 . 0	6 6	6 5	6 4	6 3	6 5	6 4	6 3	6 2	6 3	6 3	6 2	6 1	6 2	6 1	6 1	6 0	5 9		
			1 0 . 0	6 6	6 5	6 5	6 4	6 5	6 5	6 4	6 4	6 4	6 3	6 3	6 2	6 3	6 2	6 2	6 1	6 0		

