

屋内照明器具特性	
品番 (品名)	XSZR3020L
光源	L LD3420LCB1 ×1 700.0 l m
管理番号	K0192056 (0) DB 1
BZ分類	BZ1

器具効率		8 6 %	反 射 率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %		
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %		
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %		
上方光束		0 %	室指数	照明率 (X 0 . 0 1)																			Z C M
下方光束		8 6 %																					
保守率		良	0 . 6 3	0 . 6	6 9	6 3	6 0	5 7	6 9	6 3	6 0	5 7	6 7	6 3	5 9	5 7	6 6	6 2	5 9	5 7	5 6		
		中	0 . 6	0 . 8	7 5	7 0	6 6	6 4	7 4	7 0	6 6	6 4	7 3	6 9	6 6	6 3	7 2	6 8	6 5	6 3	6 2		
		否	0 . 5 6	1 . 0	7 9	7 4	7 1	6 8	7 8	7 4	7 0	6 8	7 6	7 3	7 0	6 8	7 5	7 2	6 9	6 7	6 6		
					1 . 2 5	8 2	7 8	7 5	7 2	8 1	7 7	7 4	7 2	7 9	7 6	7 4	7 2	7 8	7 5	7 3	7 1	7 0	
下方投影面積		c m ²	1 . 5	8 4	8 0	7 7	7 5	8 3	7 9	7 7	7 5	8 1	7 8	7 6	7 4	8 0	7 7	7 5	7 4	7 2			
			2 . 0	8 6	8 3	8 1	7 9	8 5	8 3	8 0	7 8	8 4	8 1	7 9	7 8	8 2	8 0	7 8	7 7	7 5			
取付 高さ	器具間隔最大限		2 . 5	8 8	8 5	8 3	8 1	8 7	8 4	8 3	8 1	8 5	8 3	8 1	8 0	8 3	8 2	8 0	7 9	7 7			
	横方向 (A)	縦方向 (B)	3 . 0	8 9	8 7	8 5	8 3	8 8	8 6	8 4	8 3	8 6	8 4	8 3	8 2	8 4	8 3	8 2	8 1	7 9			
H m	0 . 5 4 H m	0 . 5 4 H m	4 . 0	9 0	8 8	8 7	8 5	8 9	8 7	8 6	8 5	8 7	8 6	8 5	8 4	8 5	8 4	8 3	8 3	8 1			
			5 . 0	9 1	8 9	8 8	8 7	9 0	8 8	8 7	8 6	8 8	8 7	8 6	8 5	8 6	8 5	8 4	8 4	8 2			
			7 . 0	9 1	9 0	9 0	8 9	9 0	9 0	8 9	8 8	8 9	8 8	8 7	8 6	8 7	8 6	8 6	8 5	8 3			
			1 0 . 0	9 2	9 1	9 1	9 0	9 1	9 0	9 0	8 9	8 9	8 9	8 8	8 8	8 7	8 7	8 7	8 6	8 4			

