

屋内照明器具特性	
品番 (品名)	XSZR3060L
光源	LLD3410LCB1 ×1 700.0 l m
管理番号	K0192055 (0) DB 1
B Z 分類	BZ1

器具効率		90 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
上方光束		0 %	床	10 %				10 %				10 %				10 %				0 %	
下方光束		90 %		照明率 (X0.01) ZCM																	
保守率		良 中 否	0.63	0.6	70	63	59	56	69	63	59	56	68	62	58	56	66	61	58	56	54
			0.6	0.8	77	71	67	64	76	70	66	64	74	69	66	63	73	69	66	63	62
			0.56	1.0	81	75	72	69	80	75	71	69	78	74	71	68	77	73	70	68	67
				1.25	84	80	76	73	83	79	76	73	81	78	75	73	80	77	74	72	71
下方投影面積		c m ²	1.5	86	82	79	77	85	82	79	76	83	80	78	76	82	79	77	75	74	
等価発光面積			c m ²	2.0	89	86	83	81	88	85	83	81	86	84	82	80	84	82	81	79	77
取付 高さ	器具間隔最大限		2.5	91	88	86	84	90	87	85	83	88	86	84	82	86	84	83	81	80	
	横方向 (A) 縦方向 (B)		3.0	92	89	87	86	91	89	87	85	89	87	85	84	87	86	84	83	81	
H m	0.75 H m 0.75 H m		4.0	93	91	90	88	92	90	89	88	90	89	88	86	88	87	86	85	83	
			5.0	94	92	91	90	93	92	90	89	91	90	89	88	89	88	87	87	84	
			7.0	95	94	93	92	94	93	92	91	92	91	90	90	90	89	89	88	86	
			10.0	95	95	94	93	94	94	93	92	92	92	91	91	91	90	90	89	87	

