

屋内照明器具特性	
品番 (品名)	X S Z B 1 1 2 6 8
光源	L L D 2 4 0 1 L C B 1 × 1 5 0 0 . 0 l m
管理番号	K 0 1 9 3 6 8 7 (0) D B 1
B Z 分類	B Z 4 / 0 . 7 / B Z 3 / 0 . 9 / B Z 4 / 6 . 0 / B Z 5

器具効率		8 9 %	反 射 率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
上方光束 下方光束		1 1 % 7 8 %	室指数	照明率 (X 0 . 0 1) Z C M																		
保守率		良 中 否	0 . 6	5 3	4 3	3 7	3 3	5 1	4 2	3 6	3 2	4 8	4 1	3 5	3 2	4 5	3 9	3 4	3 1	2 8		
			0 . 6	6 1	5 2	4 6	4 1	5 9	5 1	4 5	4 1	5 6	4 9	4 4	4 0	5 3	4 7	4 2	3 9	3 6		
			1 . 0	6 7	5 8	5 2	4 8	6 5	5 7	5 1	4 7	6 1	5 4	4 9	4 6	5 7	5 2	4 8	4 4	4 1		
			0 . 5 6	1 . 2 5	7 1	6 4	5 8	5 3	6 9	6 2	5 7	5 3	6 5	5 9	5 5	5 1	6 1	5 6	5 3	4 9	4 6	
下方投影面積 等価発光面積		c m ² c m ²	1 . 5	7 5	6 8	6 2	5 8	7 2	6 6	6 1	5 7	6 8	6 3	5 8	5 5	6 4	6 0	5 6	5 3	4 9		
			2 . 0	7 9	7 3	6 8	6 4	7 7	7 1	6 7	6 3	7 2	6 8	6 4	6 1	6 8	6 4	6 1	5 9	5 4		
取付 高さ	器具間隔最大限		2 . 5	8 2	7 6	7 2	6 8	7 9	7 5	7 1	6 7	7 5	7 1	6 8	6 5	7 0	6 7	6 5	6 2	5 8		
	横方向 (A)	縦方向 (B)	3 . 0	8 3	7 9	7 5	7 2	8 1	7 7	7 3	7 0	7 7	7 3	7 0	6 8	7 2	7 0	6 7	6 5	6 0		
H m	1 . 0 5 H m	0 . 4 9 H m	4 . 0	8 6	8 2	7 9	7 6	8 3	8 0	7 7	7 5	7 9	7 6	7 4	7 2	7 5	7 2	7 0	6 9	6 4		
			5 . 0	8 7	8 4	8 2	7 9	8 5	8 2	8 0	7 7	8 0	7 8	7 6	7 4	7 6	7 4	7 3	7 1	6 6		
			7 . 0	8 9	8 7	8 5	8 3	8 7	8 5	8 3	8 1	8 2	8 0	7 9	7 7	7 8	7 6	7 5	7 4	6 9		
			1 0 . 0	9 0	8 9	8 7	8 6	8 8	8 7	8 5	8 4	8 4	8 2	8 1	8 0	7 9	7 8	7 7	7 6	7 1		

