

| 屋内照明器具特性 |                              |
|----------|------------------------------|
| 品番 (品名)  | XNN2561PA                    |
| 光源       | LED5000_85_1595 ×1 1595.0 lm |
| 管理番号     | K0190269 ( 0 ) DB 1          |
| BZ分類     | BZ4                          |

| 器具効率     |                     | 100 %           | 反射率    | 天井   | 80 %              |     |     |     | 70 % |     |    |     | 50 % |    |    |    | 30 % |    |    |    | 0 % |
|----------|---------------------|-----------------|--------|------|-------------------|-----|-----|-----|------|-----|----|-----|------|----|----|----|------|----|----|----|-----|
|          |                     |                 |        | 壁    | 70                | 50  | 30  | 10  | 70   | 50  | 30 | 10  | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 0 % |
|          |                     |                 |        | 床    | 10 %              |     |     |     | 10 % |     |    |     | 10 % |    |    |    | 10 % |    |    |    | 0 % |
|          |                     |                 |        | 室指数  | 照明率 ( X0.01 ) ZCM |     |     |     |      |     |    |     |      |    |    |    |      |    |    |    |     |
| 保守率      |                     | 良<br>中<br>否     | 0.83   | 0.6  | 60                | 49  | 42  | 37  | 59   | 48  | 41 | 37  | 57   | 47 | 41 | 36 | 55   | 46 | 41 | 36 | 34  |
|          |                     |                 | 0.81   | 0.8  | 71                | 60  | 53  | 48  | 69   | 59  | 52 | 47  | 67   | 58 | 52 | 47 | 64   | 57 | 51 | 47 | 45  |
|          |                     |                 | 0.77   | 1.0  | 77                | 67  | 60  | 55  | 76   | 67  | 60 | 55  | 73   | 65 | 59 | 55 | 70   | 64 | 59 | 54 | 52  |
|          |                     |                 |        | 1.25 | 83                | 74  | 68  | 63  | 81   | 73  | 67 | 62  | 79   | 72 | 66 | 62 | 76   | 70 | 65 | 61 | 59  |
| 下方投影面積   |                     | cm <sup>2</sup> | 1.5    | 87   | 79                | 73  | 68  | 85  | 78   | 72  | 68 | 82  | 76   | 71 | 67 | 80 | 74   | 70 | 66 | 64 |     |
|          |                     |                 | 等価発光面積 |      | cm <sup>2</sup>   | 2.0 | 92  | 85  | 80   | 76  | 90 | 84  | 79   | 75 | 87 | 82 | 78   | 74 | 85 | 81 | 77  |
| 取付<br>高さ | 器具間隔最大限             |                 | 2.5    | 95   | 89                | 85  | 81  | 93  | 88   | 84  | 80 | 91  | 86   | 83 | 79 | 88 | 84   | 81 | 78 | 76 |     |
|          | 横方向 ( A ) 縦方向 ( B ) |                 | 3.0    | 97   | 92                | 88  | 85  | 96  | 91   | 87  | 84 | 93  | 89   | 86 | 83 | 90 | 87   | 84 | 82 | 79 |     |
| H m      | 1.19 H m            | 1.19 H m        | 4.0    | 100  | 96                | 93  | 90  | 98  | 95   | 92  | 89 | 96  | 93   | 90 | 88 | 93 | 91   | 89 | 87 | 84 |     |
|          |                     |                 | 5.0    | 102  | 98                | 96  | 93  | 100 | 97   | 95  | 92 | 98  | 95   | 93 | 91 | 95 | 93   | 91 | 89 | 87 |     |
|          |                     |                 | 7.0    | 103  | 101               | 99  | 97  | 102 | 100  | 98  | 96 | 100 | 98   | 96 | 95 | 97 | 96   | 94 | 93 | 90 |     |
|          |                     |                 | 10.0   | 105  | 103               | 102 | 100 | 104 | 102  | 101 | 99 | 101 | 100  | 99 | 97 | 99 | 98   | 97 | 96 | 93 |     |

