

| 屋内照明器具特性 |                         |
|----------|-------------------------|
| 品番 (品名)  | XS Z D1 0 0 0 L         |
| 光源       | LLD2400LCB1 ×1 500.0 lm |
| 管理番号     | K0191450 ( 0 ) DB 1     |
| B Z 分類   | BZ2                     |

| 器具効率   |          | 95 %            | 反射率  | 天井   | 80 % |      |                    |    | 70 % |      |    |    | 50 % |      |    |    | 30 % |      |    |    | 0 % |     |
|--------|----------|-----------------|------|------|------|------|--------------------|----|------|------|----|----|------|------|----|----|------|------|----|----|-----|-----|
|        |          |                 |      | 壁    | 70   | 50   | 30                 | 10 | 70   | 50   | 30 | 10 | 70   | 50   | 30 | 10 | 70   | 50   | 30 | 10 | 0 % |     |
|        |          |                 |      |      | 床    | 10 % |                    |    |      | 10 % |    |    |      | 10 % |    |    |      | 10 % |    |    |     | 0 % |
|        |          |                 |      |      |      | 室指数  | 照明率 ( X0.01 ) Z CM |    |      |      |    |    |      |      |    |    |      |      |    |    |     |     |
| 保守率    |          | 良<br>中<br>否     | 0.67 | 0.6  | 63   | 54   | 48                 | 43 | 62   | 53   | 47 | 43 | 60   | 52   | 47 | 43 | 58   | 51   | 47 | 43 | 41  |     |
|        |          |                 | 0.63 | 0.8  | 73   | 65   | 59                 | 55 | 72   | 64   | 59 | 55 | 70   | 63   | 58 | 54 | 68   | 62   | 57 | 54 | 53  |     |
|        |          |                 | 0.56 | 1.0  | 79   | 72   | 66                 | 62 | 78   | 71   | 66 | 62 | 76   | 70   | 65 | 62 | 74   | 68   | 65 | 61 | 60  |     |
|        |          |                 |      | 1.25 | 84   | 77   | 73                 | 69 | 83   | 77   | 72 | 69 | 80   | 75   | 71 | 68 | 78   | 74   | 70 | 68 | 66  |     |
| 下方投影面積 |          | cm <sup>2</sup> | 1.5  | 87   | 81   | 77   | 73                 | 86 | 80   | 76   | 73 | 83 | 79   | 75   | 72 | 81 | 78   | 74   | 72 | 70 |     |     |
|        |          |                 | 2.0  | 91   | 86   | 82   | 79                 | 90 | 85   | 82   | 79 | 87 | 84   | 81   | 78 | 85 | 82   | 80   | 77 | 75 |     |     |
| 等価発光面積 |          | cm <sup>2</sup> | 2.5  | 93   | 89   | 86   | 83                 | 92 | 88   | 85   | 83 | 90 | 87   | 84   | 82 | 88 | 85   | 83   | 81 | 79 |     |     |
|        |          |                 | 3.0  | 95   | 91   | 89   | 86                 | 94 | 91   | 88   | 86 | 91 | 89   | 87   | 85 | 89 | 87   | 85   | 83 | 81 |     |     |
| H m    | 1.26 H m | 1.26 H m        | 4.0  | 97   | 94   | 92   | 90                 | 96 | 93   | 91   | 89 | 93 | 91   | 90   | 88 | 91 | 90   | 88   | 87 | 84 |     |     |
|        |          |                 | 5.0  | 98   | 96   | 94   | 92                 | 97 | 95   | 93   | 91 | 95 | 93   | 91   | 90 | 92 | 91   | 90   | 89 | 86 |     |     |
|        |          |                 | 7.0  | 99   | 98   | 96   | 95                 | 98 | 97   | 95   | 94 | 96 | 95   | 94   | 93 | 94 | 93   | 92   | 91 | 88 |     |     |
|        |          |                 | 10.0 | 100  | 99   | 98   | 97                 | 99 | 98   | 97   | 96 | 97 | 96   | 95   | 94 | 95 | 94   | 93   | 93 | 90 |     |     |

