

屋内照明器具特性	
品番 (品名)	XS Z D1 0 0 1 V
光源	LLD2401VCB1 ×1 500.0 lm
管理番号	K0191442 (0) DB 1
BZ分類	BZ2 / 8.5 / BZ1

器具効率		89 %	反射率	天井	80 %				70 %				50 %				30 %				0 %		
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %		
上方光束		0 %		床	10 %				10 %				10 %				10 %				0 %		
下方光束		89 %		室指数																			
			照明率 (X0.01)																			Z CM	
保守率		良 中 否	0.67	0.6	60	52	46	42	59	51	46	42	58	50	45	42	56	50	45	42	40		
			0.63	0.8	70	62	57	53	69	61	57	53	67	60	56	53	65	60	56	52	51		
			0.56	1.0	75	69	64	60	74	68	63	60	72	67	63	60	70	66	62	59	58		
				1.25	80	74	70	66	79	73	69	66	77	72	69	66	75	71	68	65	64		
下方投影面積		cm ²	1.5	83	78	74	70	82	77	73	70	79	75	72	70	78	74	71	69	67			
等価発光面積		cm ²	2.0	86	82	79	76	85	81	78	76	83	80	77	75	81	78	76	74	72			
取付 高さ	器具間隔最大限		2.5	88	85	82	80	87	84	82	79	85	83	80	78	83	81	79	77	76			
	横方向 (A) 縦方向 (B)		3.0	90	87	84	82	89	86	84	82	87	84	82	81	85	83	81	80	78			
H m	1.25 H m	1.25 H m	4.0	92	89	87	85	91	88	87	85	88	87	85	84	86	85	84	83	80			
			5.0	93	91	89	88	92	90	88	87	89	88	87	86	88	86	85	84	82			
			7.0	94	92	91	90	93	91	90	89	91	90	89	88	89	88	87	86	84			
			10.0	95	94	93	92	94	93	92	91	92	91	90	89	90	89	88	88	85			

