

屋内照明器具特性	
品番 (品名)	XNN1531PV
光源	LED3500_85_1080 ×1 1080.0 lm
管理番号	K0192368 (0) DB 1
BZ分類	BZ5 / 0.7 / BZ4

器具効率		1 0 0 %	反射率	天井	8 0 %					7 0 %					5 0 %					3 0 %					0 %			
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %							
				床	1 0 %					1 0 %					1 0 %					1 0 %					0 %			
上方光束		0 %	室指数	照明率 (X 0 . 0 1)																				Z C M				
下方光束				1 0 0 %																								
保守率		良 中 否	0 . 8 3	0 . 6	5 8	4 7	3 9	3 4	5 7	4 6	3 9	3 4	5 5	4 5	3 8	3 3	5 3	4 4	3 8	3 3	3 1							
			0 . 8 1	0 . 8	6 9	5 8	5 0	4 4	6 7	5 7	5 0	4 4	6 5	5 5	4 9	4 4	6 2	5 4	4 8	4 4	4 2							
			0 . 7 7	1 . 0	7 5	6 5	5 8	5 2	7 4	6 4	5 7	5 2	7 1	6 3	5 6	5 2	6 8	6 1	5 6	5 1	4 9							
				1 . 2 5	8 1	7 2	6 5	6 0	8 0	7 1	6 5	5 9	7 7	6 9	6 4	5 9	7 4	6 8	6 3	5 9	5 6							
下方投影面積		c m ²	1 . 5	8 5	7 7	7 0	6 5	8 4	7 6	7 0	6 5	8 1	7 4	6 9	6 4	7 8	7 2	6 8	6 4	6 1								
等価発光面積			c m ²	2 . 0	9 1	8 4	7 8	7 3	8 9	8 3	7 7	7 3	8 6	8 1	7 6	7 2	8 3	7 9	7 5	7 1	6 9							
取付 高さ	器具間隔最大限		2 . 5	9 4	8 8	8 3	7 9	9 2	8 7	8 2	7 8	9 0	8 5	8 1	7 7	8 7	8 3	8 0	7 6	7 4								
	横方向 (A)		縦方向 (B)	3 . 0	9 6	9 1	8 7	8 3	9 5	9 0	8 6	8 2	9 2	8 8	8 4	8 1	8 9	8 6	8 3	8 0	7 8							
H m	1 . 2 3 H m	1 . 2 3 H m	4 . 0	9 9	9 5	9 2	8 8	9 8	9 4	9 1	8 8	9 5	9 2	8 9	8 6	9 2	9 0	8 7	8 5	8 3								
			5 . 0	1 0 1	9 8	9 5	9 2	1 0 0	9 7	9 4	9 1	9 7	9 4	9 2	9 0	9 4	9 2	9 0	8 8	8 6								
			7 . 0	1 0 3	1 0 1	9 8	9 6	1 0 2	9 9	9 7	9 5	9 9	9 7	9 5	9 4	9 7	9 5	9 4	9 2	8 9								
			1 0 . 0	1 0 5	1 0 3	1 0 1	1 0 0	1 0 3	1 0 2	1 0 0	9 9	1 0 1	9 9	9 8	9 7	9 8	9 7	9 6	9 5	9 2								

