

屋内照明器具特性	
品番 (品名)	X S Z D 3 0 0 1 V
光源	L L D 3 4 0 1 V C B 1 × 1 7 0 0 . 0 l m
管理番号	K 0 1 9 1 4 4 1 (0) D B 1
B Z 分類	B Z 2 / 8 . 5 / B Z 1

器具効率		9 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
上方光束 下方光束		0 % 9 0 %	室指数	照明率 (X 0 . 0 1) Z C M																		
保守率		良 中 否	0 . 6 7	0 . 6	6 1	5 2	4 6	4 2	6 0	5 1	4 6	4 2	5 8	5 1	4 6	4 2	5 6	5 0	4 5	4 2	4 1	
			0 . 6 3	0 . 8	7 0	6 2	5 7	5 3	6 9	6 2	5 7	5 3	6 7	6 1	5 6	5 3	6 5	6 0	5 6	5 3	5 1	
			0 . 5 6	1 . 0	7 6	6 9	6 4	6 1	7 5	6 8	6 4	6 0	7 3	6 7	6 3	6 0	7 1	6 6	6 3	6 0	5 8	
				1 . 2 5	8 0	7 5	7 0	6 7	7 9	7 4	7 0	6 7	7 7	7 3	6 9	6 6	7 5	7 1	6 8	6 6	6 4	
下方投影面積		c m ²	1 . 5	8 3	7 8	7 4	7 1	8 2	7 7	7 4	7 1	8 0	7 6	7 3	7 0	7 8	7 5	7 2	7 0	6 8		
等価発光面積		c m ²	2 . 0	8 7	8 3	7 9	7 7	8 6	8 2	7 9	7 6	8 4	8 1	7 8	7 5	8 2	7 9	7 7	7 5	7 3		
取付 高さ	器具間隔最大限		2 . 5	8 9	8 6	8 3	8 0	8 8	8 5	8 2	8 0	8 6	8 3	8 1	7 9	8 4	8 2	8 0	7 8	7 6		
	横方向 (A) 縦方向 (B)		3 . 0	9 1	8 8	8 5	8 3	8 9	8 7	8 4	8 2	8 7	8 5	8 3	8 1	8 5	8 3	8 2	8 0	7 8		
H m	1 . 2 6 H m	1 . 2 6 H m	4 . 0	9 2	9 0	8 8	8 6	9 1	8 9	8 7	8 6	8 9	8 7	8 6	8 4	8 7	8 6	8 4	8 3	8 1		
			5 . 0	9 3	9 1	9 0	8 8	9 2	9 1	8 9	8 8	9 0	8 9	8 7	8 6	8 8	8 7	8 6	8 5	8 3		
			7 . 0	9 5	9 3	9 2	9 1	9 3	9 2	9 1	9 0	9 1	9 0	8 9	8 8	8 9	8 9	8 8	8 7	8 5		
			1 0 . 0	9 5	9 4	9 3	9 3	9 4	9 3	9 3	9 2	9 2	9 2	9 1	9 0	9 0	9 0	8 9	8 9	8 6		

