

| 屋内照明器具特性 |                          |
|----------|--------------------------|
| 品番 (品名)  | XSZP1067V+LGK9100B       |
| 光源       | LLD2411VCB1 ×1 500.0 l m |
| 管理番号     | K0191402 ( 0 ) DB 1      |
| B Z 分類   | BZ1                      |

| 器具効率   |           | 95 %             | 反射率       | 天井            | 80 % |     |     |     | 70 % |     |     |     | 50 % |    |    |    | 30 % |    |    |    | 0 % |       |  |
|--------|-----------|------------------|-----------|---------------|------|-----|-----|-----|------|-----|-----|-----|------|----|----|----|------|----|----|----|-----|-------|--|
|        |           |                  |           | 壁             | 70   | 50  | 30  | 10  | 70   | 50  | 30  | 10  | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 0 % |       |  |
|        |           |                  |           | 床             | 10 % |     |     |     | 10 % |     |     |     | 10 % |    |    |    | 10 % |    |    |    | 0 % |       |  |
| 上方光束   |           | 0 %              | 室指数       | 照明率 ( X0.01 ) |      |     |     |     |      |     |     |     |      |    |    |    |      |    |    |    |     | Z C M |  |
| 下方光束   |           | 95 %             |           |               |      |     |     |     |      |     |     |     |      |    |    |    |      |    |    |    |     |       |  |
| 保守率    |           | 良                | 0.67      | 0.6           | 87   | 82  | 80  | 78  | 86   | 82  | 80  | 78  | 85   | 82 | 79 | 78 | 84   | 81 | 79 | 77 | 77  |       |  |
|        |           | 中                | 0.63      | 0.8           | 91   | 87  | 84  | 83  | 90   | 87  | 84  | 82  | 89   | 86 | 84 | 82 | 88   | 85 | 83 | 82 | 81  |       |  |
|        |           | 否                | 0.56      | 1.0           | 93   | 90  | 87  | 86  | 93   | 89  | 87  | 85  | 91   | 89 | 87 | 85 | 90   | 88 | 86 | 85 | 84  |       |  |
|        |           | 0.56             | 1.25      | 95            | 92   | 90  | 88  | 95  | 92   | 90  | 88  | 93  | 91   | 89 | 88 | 92 | 90   | 88 | 87 | 86 |     |       |  |
| 下方投影面積 |           | c m <sup>2</sup> |           | 1.5           | 97   | 94  | 92  | 90  | 96   | 93  | 91  | 90  | 94   | 92 | 91 | 89 | 93   | 91 | 90 | 89 | 87  |       |  |
| 等価発光面積 |           | c m <sup>2</sup> |           | 2.0           | 98   | 96  | 94  | 93  | 97   | 95  | 94  | 92  | 96   | 94 | 93 | 92 | 94   | 93 | 92 | 91 | 89  |       |  |
| 取付高さ   | 器具間隔最大限   |                  |           | 2.5           | 99   | 98  | 96  | 95  | 98   | 97  | 95  | 94  | 97   | 95 | 94 | 93 | 95   | 94 | 93 | 92 | 90  |       |  |
|        | 横方向 ( A ) |                  | 縦方向 ( B ) | 3.0           | 100  | 98  | 97  | 96  | 99   | 98  | 96  | 95  | 97   | 96 | 95 | 94 | 96   | 95 | 94 | 93 | 91  |       |  |
| H m    | 0.78 H m  |                  | 0.78 H m  | 4.0           | 101  | 100 | 99  | 98  | 100  | 99  | 98  | 97  | 98   | 97 | 96 | 96 | 96   | 96 | 95 | 94 | 92  |       |  |
|        |           |                  |           | 5.0           | 101  | 100 | 99  | 99  | 100  | 99  | 99  | 98  | 98   | 98 | 97 | 96 | 97   | 96 | 96 | 95 | 93  |       |  |
|        |           |                  |           | 7.0           | 102  | 101 | 101 | 100 | 101  | 100 | 100 | 99  | 99   | 98 | 98 | 97 | 97   | 97 | 96 | 96 | 94  |       |  |
|        |           |                  |           | 10.0          | 102  | 102 | 101 | 101 | 101  | 101 | 100 | 100 | 99   | 99 | 99 | 98 | 97   | 97 | 97 | 97 | 94  |       |  |

