

| 屋内照明器具特性 |                              |
|----------|------------------------------|
| 品番 (品名)  | XNW2 5 3 1 B V               |
| 光源       | LED3500_85_1685 ×1 1685.0 lm |
| 管理番号     | K0167857 ( 0 ) DB 1          |
| BZ分類     | BZ1                          |

| 器具効率           |                     | 100 %               | 反射率  | 天井                | 80 % |     |     |     |     | 70 % |     |     |     |     | 50 % |     |     |     |    | 30 % |     |  |  |  | 0 % |
|----------------|---------------------|---------------------|------|-------------------|------|-----|-----|-----|-----|------|-----|-----|-----|-----|------|-----|-----|-----|----|------|-----|--|--|--|-----|
|                |                     |                     |      | 壁                 | 70   | 50  | 30  | 10  | 70  | 50   | 30  | 10  | 70  | 50  | 30   | 10  | 70  | 50  | 30 | 10   | 0 % |  |  |  |     |
|                |                     |                     |      | 床                 | 10 % |     |     |     |     | 10 % |     |     |     |     | 10 % |     |     |     |    | 10 % |     |  |  |  | 0 % |
| 上方光束<br>下方光束   |                     | 100 %               | 室指数  | 照明率 ( X0.01 ) ZCM |      |     |     |     |     |      |     |     |     |     |      |     |     |     |    |      |     |  |  |  |     |
| 保守率            |                     | 良<br>中<br>否         | 0.83 | 0.6               | 76   | 68  | 63  | 59  | 75  | 67   | 63  | 59  | 73  | 67  | 62   | 59  | 72  | 66  | 62 | 59   | 58  |  |  |  |     |
|                |                     |                     | 0.81 | 0.8               | 84   | 77  | 73  | 69  | 83  | 77   | 72  | 69  | 81  | 76  | 72   | 69  | 80  | 75  | 71 | 69   | 67  |  |  |  |     |
|                |                     |                     | 0.77 | 1.0               | 89   | 83  | 79  | 76  | 88  | 83   | 79  | 75  | 86  | 81  | 78   | 75  | 85  | 80  | 77 | 75   | 73  |  |  |  |     |
|                |                     |                     | 0.77 | 1.25              | 93   | 88  | 84  | 81  | 92  | 87   | 84  | 81  | 90  | 86  | 83   | 80  | 88  | 85  | 82 | 80   | 78  |  |  |  |     |
| 下方投影面積         |                     | cm <sup>2</sup>     | 1.5  | 96                | 91   | 88  | 85  | 95  | 90  | 87   | 84  | 93  | 89  | 86  | 84   | 91  | 88  | 85  | 83 | 81   |     |  |  |  |     |
| 等価発光面積         |                     |                     | 2.0  | 99                | 95   | 92  | 90  | 98  | 95  | 92   | 89  | 96  | 93  | 91  | 88   | 94  | 91  | 89  | 88 | 86   |     |  |  |  |     |
| 取付<br>高さ       | 器具間隔最大限             |                     | 2.5  | 101               | 98   | 95  | 93  | 100 | 97  | 95   | 92  | 98  | 95  | 93  | 91   | 96  | 94  | 92  | 90 | 88   |     |  |  |  |     |
|                | 横方向 (A) 縦方向 (B)     |                     | 3.0  | 102               | 100  | 97  | 95  | 101 | 99  | 96   | 95  | 99  | 97  | 95  | 93   | 97  | 95  | 94  | 92 | 90   |     |  |  |  |     |
| H <sub>m</sub> | 1.04 H <sub>m</sub> | 1.04 H <sub>m</sub> | 4.0  | 104               | 102  | 100 | 98  | 103 | 101 | 99   | 97  | 100 | 99  | 97  | 96   | 98  | 97  | 96  | 95 | 92   |     |  |  |  |     |
|                |                     |                     | 5.0  | 105               | 103  | 101 | 100 | 104 | 102 | 101  | 99  | 101 | 100 | 99  | 98   | 99  | 98  | 97  | 96 | 94   |     |  |  |  |     |
|                |                     |                     | 7.0  | 106               | 104  | 103 | 102 | 105 | 103 | 102  | 101 | 102 | 101 | 100 | 100  | 100 | 99  | 99  | 98 | 95   |     |  |  |  |     |
|                |                     |                     | 10.0 | 106               | 106  | 105 | 104 | 105 | 104 | 104  | 103 | 103 | 102 | 102 | 101  | 101 | 100 | 100 | 99 | 97   |     |  |  |  |     |

