

屋内照明器具特性	
品番 (品名)	XS Z P 1 5 0 7 L
光源	LLD2401LCB1 ×1 500.0 lm
管理番号	K0191399 (0) DB 1
B Z 分類	BZ3 / 1.1 / BZ2 / 1.8 / BZ3 / 8.5 / BZ2

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
上方光束 下方光束		1 0 0 %	室指数	照明率 (X 0 . 0 1) Z C M																		
保守率		良 中 否	0 . 6	6 5	5 4	4 7	4 3	6 3	5 4	4 7	4 3	6 1	5 3	4 7	4 2	5 9	5 2	4 6	4 2	4 1		
			0 . 6 7	7 5	6 5	5 9	5 4	7 4	6 5	5 9	5 4	7 1	6 4	5 8	5 4	6 9	6 2	5 7	5 4	5 2		
			1 . 0	8 1	7 3	6 7	6 2	8 0	7 2	6 6	6 2	7 7	7 1	6 6	6 2	7 5	6 9	6 5	6 1	5 9		
			0 . 6 3	1 . 2 5	8 7	7 9	7 4	6 9	8 5	7 8	7 3	6 9	8 3	7 7	7 2	6 9	8 0	7 5	7 1	6 8	6 6	
下方投影面積		c m ²	1 . 5	9 0	8 4	7 8	7 4	8 9	8 3	7 8	7 4	8 6	8 1	7 7	7 3	8 4	7 9	7 6	7 3	7 1		
等価発光面積			c m ²	2 . 0	9 5	8 9	8 5	8 1	9 3	8 8	8 4	8 1	9 1	8 7	8 3	8 0	8 8	8 5	8 2	7 9	7 7	
取付 高さ	器具間隔最大限		2 . 5	9 7	9 3	8 9	8 6	9 6	9 2	8 8	8 5	9 4	9 0	8 7	8 4	9 1	8 8	8 6	8 3	8 1		
	横方向 (A) 縦方向 (B)		3 . 0	9 9	9 5	9 2	8 9	9 8	9 4	9 1	8 9	9 5	9 2	9 0	8 7	9 3	9 1	8 8	8 6	8 4		
H m	1 . 3 1 H m	1 . 3 1 H m	4 . 0	1 0 2	9 9	9 6	9 3	1 0 0	9 7	9 5	9 3	9 8	9 5	9 3	9 1	9 5	9 4	9 2	9 0	8 8		
			5 . 0	1 0 3	1 0 0	9 8	9 6	1 0 2	9 9	9 7	9 5	9 9	9 7	9 6	9 4	9 7	9 5	9 4	9 2	9 0		
			7 . 0	1 0 4	1 0 3	1 0 1	9 9	1 0 3	1 0 2	1 0 0	9 9	1 0 1	9 9	9 8	9 7	9 9	9 7	9 6	9 5	9 3		
			1 0 . 0	1 0 6	1 0 4	1 0 3	1 0 2	1 0 4	1 0 3	1 0 2	1 0 1	1 0 2	1 0 1	1 0 0	9 9	1 0 0	9 9	9 8	9 7	9 5		

