

屋内照明器具特性	
品番 (品名)	XSZP1507N+LGK9100B
光源	LLD2401NCB1 ×1 500.0 lm
管理番号	K0191400 (0) DB 1
BZ分類	BZ1

器具効率		78 %	反射率	天井	80 %					70 %					50 %					30 %					0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
				床	10 %					10 %					10 %					10 %					0 %
				室指数	照明率 (X0.01)																			Z	CM
保守率		良 中 否	0.67	0.6	56	49	44	41	55	48	44	41	53	48	44	41	52	47	44	41	40				
			0.63	0.8	63	57	53	50	62	57	53	50	61	56	52	50	59	55	52	50	48				
			0.56	1.0	68	62	59	56	67	62	58	56	65	61	58	55	64	60	57	55	54				
			1.25	71	67	63	61	70	66	63	60	69	65	62	60	67	64	62	60	58					
下方投影面積		cm ²	1.5	73	69	66	64	72	69	66	63	71	68	65	63	69	67	64	63	61					
等価発光面積			2.0	76	73	70	68	75	72	70	68	73	71	69	67	72	70	68	67	65					
取付 高さ	器具間隔最大限		2.5	78	75	73	71	77	74	72	71	75	73	71	70	74	72	70	69	67					
	横方向 (A)		縦方向 (B)		3.0	79	77	75	73	78	76	74	72	76	74	73	72	75	73	72	71	69			
H _m	1.30 H _m	1.30 H _m	4.0	80	78	77	75	79	78	76	75	78	76	75	74	76	75	74	73	71					
			5.0	81	80	78	77	80	79	78	76	78	77	76	75	77	76	75	74	72					
			7.0	82	81	80	79	81	80	79	78	79	78	78	77	78	77	76	76	74					
			10.0	83	82	81	80	82	81	80	80	80	79	79	78	78	78	77	77	75					

