

| 屋内照明器具特性 |                              |
|----------|------------------------------|
| 品番 (品名)  | XNN5 5 6 7 S V               |
| 光源       | LED3500_80_5230 ×1 5230.0 lm |
| 管理番号     | K0179660 ( 0 ) DB 1          |
| B Z 分類   | BZ1                          |

| 器具効率     |           | 100 %           | 反射率             | 天井   | 80 %              |     |     |     | 70 % |     |     |     | 50 % |     |     |     | 30 % |     |     |     | 0 % |    |  |
|----------|-----------|-----------------|-----------------|------|-------------------|-----|-----|-----|------|-----|-----|-----|------|-----|-----|-----|------|-----|-----|-----|-----|----|--|
|          |           |                 |                 | 壁    | 70                | 50  | 30  | 10  | 70   | 50  | 30  | 10  | 70   | 50  | 30  | 10  | 70   | 50  | 30  | 10  | 0 % |    |  |
|          |           |                 |                 | 床    | 10 %              |     |     |     | 10 % |     |     |     | 10 % |     |     |     | 10 % |     |     |     | 0 % |    |  |
| 上方光束     |           | 0 %             | 100 %           | 室指数  | 照明率 ( X0.01 ) ZCM |     |     |     |      |     |     |     |      |     |     |     |      |     |     |     |     |    |  |
| 下方光束     |           |                 |                 |      |                   |     |     |     |      |     |     |     |      |     |     |     |      |     |     |     |     |    |  |
| 保守率      |           | 良<br>中<br>否     | 0.76            | 0.6  | 80                | 72  | 68  | 65  | 79   | 72  | 68  | 65  | 77   | 71  | 67  | 65  | 76   | 71  | 67  | 64  | 63  |    |  |
|          |           |                 | 0.72            | 0.8  | 87                | 81  | 77  | 74  | 86   | 81  | 77  | 74  | 85   | 80  | 76  | 74  | 83   | 79  | 76  | 73  | 72  |    |  |
|          |           |                 | 0.64            | 1.0  | 92                | 86  | 83  | 80  | 91   | 86  | 82  | 80  | 89   | 85  | 82  | 79  | 87   | 84  | 81  | 79  | 77  |    |  |
|          |           |                 |                 | 1.25 | 95                | 91  | 87  | 85  | 94   | 90  | 87  | 84  | 93   | 89  | 86  | 84  | 91   | 88  | 85  | 83  | 82  |    |  |
| 下方投影面積   |           | cm <sup>2</sup> | 1.5             | 98   | 93                | 90  | 88  | 97  | 93   | 90  | 87  | 95  | 91   | 89  | 87  | 93  | 90   | 88  | 86  | 85  |     |    |  |
| 等価発光面積   |           |                 | cm <sup>2</sup> | 2.0  | 100               | 97  | 94  | 92  | 99   | 96  | 94  | 92  | 97   | 95  | 93  | 91  | 95   | 93  | 92  | 90  | 88  |    |  |
|          |           |                 |                 | 2.5  | 102               | 99  | 97  | 95  | 101  | 98  | 96  | 94  | 99   | 97  | 95  | 93  | 97   | 95  | 94  | 92  | 90  |    |  |
| 取付<br>高さ | 器具間隔最大限   |                 | 2.5             | 102  | 99                | 97  | 95  | 101 | 98   | 96  | 94  | 99  | 97   | 95  | 93  | 97  | 95   | 94  | 92  | 90  |     |    |  |
|          | 横方向 ( A ) |                 | 縦方向 ( B )       |      | 3.0               | 103 | 101 | 99  | 97   | 102 | 100 | 98  | 96   | 100 | 98  | 97  | 95   | 98  | 97  | 95  | 94  | 92 |  |
| H m      | 1.06 H m  |                 | 1.06 H m        |      | 4.0               | 105 | 103 | 101 | 100  | 103 | 102 | 100 | 99   | 101 | 100 | 99  | 97   | 99  | 98  | 97  | 96  | 94 |  |
|          |           |                 |                 |      | 5.0               | 105 | 104 | 102 | 101  | 104 | 103 | 102 | 100  | 102 | 101 | 100 | 99   | 100 | 99  | 98  | 97  | 95 |  |
|          |           |                 |                 |      | 7.0               | 106 | 105 | 104 | 103  | 105 | 104 | 103 | 102  | 103 | 102 | 101 | 101  | 101 | 100 | 100 | 99  | 96 |  |
|          |           |                 |                 |      | 10.0              | 107 | 106 | 105 | 105  | 106 | 105 | 104 | 104  | 104 | 103 | 102 | 102  | 101 | 101 | 101 | 100 | 97 |  |

