

屋内照明器具特性	
品番 (品名)	XS Z P 3 5 0 7 N
光源	LLD3401NCB1 ×1 700.0 lm
管理番号	K0191393 (0) DB 1
B Z 分類	BZ3 / 1.1 / BZ2 / 1.8 / BZ3

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) ZCM																
保守率		良 中 否	0.69	0.6	64	54	47	43	63	53	47	42	61	52	47	42	59	52	46	42	41
			0.67	0.8	75	65	59	54	73	65	59	54	71	63	58	54	69	62	57	54	52
			0.63	1.0	81	73	67	62	80	72	66	62	77	71	66	62	75	69	65	61	59
				1.25	87	79	74	69	85	78	73	69	83	77	72	69	80	75	71	68	66
下方投影面積		cm ²	1.5	90	83	78	74	89	83	78	74	86	81	77	73	84	79	76	73	71	
			等価発光面積		cm ²	2.0	95	89	85	81	93	88	84	81	91	87	83	80	88	85	82
取付 高さ	器具間隔最大限		2.5	97	93	89	86	96	92	88	85	94	90	87	84	91	88	86	83	81	
	横方向 (A) 縦方向 (B)		3.0	99	95	92	89	98	94	91	88	95	92	90	87	93	91	88	86	84	
H m	1.33 H m 1.33 H m		4.0	102	99	96	93	100	97	95	93	98	95	93	91	95	94	92	90	88	
			5.0	103	100	98	96	102	99	97	95	99	97	96	94	97	95	94	92	90	
			7.0	104	103	101	99	103	102	100	98	101	99	98	97	99	97	96	95	93	
			10.0	106	104	103	102	104	103	102	101	102	101	100	99	100	99	98	97	95	

