

屋内照明器具特性	
品番 (品名)	XSZR1000N
光源	LLD2400NCB1 ×1 500.0 lm
管理番号	K0192051 (0) DB 1
BZ分類	BZ2

器具効率		72 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01)																Z C M
保守率		良 中 否	0.63	0.6	50	43	39	36	49	43	39	36	48	42	38	36	46	41	38	36	34
			0.6	0.8	56	50	46	43	55	50	46	43	54	49	46	43	53	48	45	43	42
			0.56	1.0	60	55	51	48	59	54	51	48	58	54	50	48	56	53	50	48	46
				1.25	64	59	55	53	63	58	55	53	61	57	55	52	60	56	54	52	51
下方投影面積 等価発光面積		c m ²		1.5	66	62	58	56	65	61	58	56	63	60	57	55	62	59	57	55	53
				2.0	69	65	63	60	68	65	62	60	66	64	61	59	65	62	60	59	57
				2.5	71	68	65	63	70	67	65	63	68	66	64	62	66	64	63	61	60
				3.0	72	69	67	65	71	69	67	65	69	67	65	64	67	66	64	63	62
H m	1.08 H m	1.08 H m		4.0	73	71	69	68	72	70	69	67	71	69	68	66	69	68	67	66	64
				5.0	74	72	71	70	73	72	70	69	71	70	69	68	70	69	68	67	65
				7.0	75	74	73	72	74	73	72	71	72	72	71	70	71	70	69	69	67
				10.0	76	75	74	73	75	74	73	73	73	73	72	71	72	71	71	70	68

