

屋内照明器具特性	
品番 (品名)	XSZR1040N
光源	L LD2420NCB1 ×1 500.0 l m
管理番号	K0192053 (0) DB 1
B Z 分類	BZ1

器具効率		87 %	反 射 率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
上方光束		0 %		床	10 %				10 %				10 %				10 %				0 %
下方光束		87 %		室指数	照明率 (X0.01) ZCM																
保守率		良	0.63	0.6	69	63	59	57	69	63	59	57	67	62	59	57	66	62	59	56	55
		中	0.6	0.8	75	70	66	64	74	70	66	64	73	69	66	63	72	68	65	63	62
		否	1.0	79	74	71	68	78	74	70	68	77	73	70	68	75	72	69	67	66	
		0.56	1.25	82	78	75	72	81	77	74	72	79	76	74	72	78	75	73	71	70	
下方投影面積		c m ²		1.5	84	80	77	75	83	80	77	75	81	78	76	74	80	77	75	74	72
等価発光面積		c m ²		2.0	86	83	81	79	86	83	81	79	84	81	80	78	82	80	79	77	76
取付 高さ	器具間隔最大限			2.5	88	85	83	82	87	85	83	81	85	83	82	80	84	82	81	79	78
	横方向 (A)		縦方向 (B)	3.0	89	87	85	83	88	86	84	83	86	85	83	82	84	83	82	81	79
H m	0.55 H m		0.55 H m	4.0	90	89	87	86	89	88	86	85	87	86	85	84	86	85	84	83	81
				5.0	91	90	88	87	90	89	88	87	88	87	86	85	86	85	85	84	82
				7.0	92	91	90	89	91	90	89	88	89	88	87	87	87	87	86	85	83
				10.0	92	92	91	90	91	91	90	90	89	89	89	88	88	87	87	87	84

