

屋内照明器具特性	
品番 (品名)	XSZR3000L
光源	LLD3400LCB1 ×1 700.0 lm
管理番号	K0192054 (0) DB 1
BZ分類	BZ2

器具効率		70 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) ZCM																
保守率		良 中 否	0.63	0.6	48	42	38	35	48	41	37	35	46	41	37	35	45	40	37	35	33
			0.6	0.8	55	49	45	42	54	48	45	42	52	48	44	42	51	47	44	42	40
			0.56	1.0	59	53	50	47	58	53	49	47	56	52	49	46	55	51	48	46	45
				1.25	62	57	54	51	61	57	54	51	59	56	53	51	58	55	52	50	49
下方投影面積		cm ²		1.5	64	60	57	54	63	59	56	54	62	58	56	54	60	57	55	53	52
等価発光面積			cm ²	2.0	67	64	61	59	66	63	60	58	64	62	60	58	63	61	59	57	56
取付高さ	器具間隔最大限			2.5	69	66	63	61	68	65	63	61	66	64	62	60	64	63	61	60	58
	横方向 (A)		縦方向 (B)	3.0	70	67	65	63	69	67	65	63	67	65	64	62	66	64	63	61	60
Hm	1.09Hm		1.09Hm	4.0	71	69	68	66	70	69	67	66	69	67	66	65	67	66	65	64	62
				5.0	72	70	69	68	71	70	68	67	69	68	67	66	68	67	66	65	63
				7.0	73	72	71	70	72	71	70	69	70	70	69	68	69	68	67	67	65
				10.0	74	73	72	71	73	72	71	71	71	71	70	69	70	69	69	68	66

