

屋内照明器具特性	
品番 (品名)	XSZR1060N
光源	LLD2410NCB1 ×1 500.0 l m
管理番号	K0192052 (0) DB 1
BZ分類	BZ1

器具効率		9 1 %	反 射 率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %		
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %		
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %		
上方光束		0 %	室指数	照明率 (X 0 . 0 1)																			Z C M
下方光束		9 1 %																					
保守率		良	0 . 6 3	0 . 6	7 1	6 4	6 0	5 7	7 0	6 3	5 9	5 7	6 8	6 3	5 9	5 6	6 7	6 2	5 9	5 6	5 5		
		中	0 . 6	0 . 8	7 7	7 2	6 7	6 5	7 7	7 1	6 7	6 4	7 5	7 0	6 7	6 4	7 4	6 9	6 6	6 4	6 3		
		否	0 . 5 6	1 . 0	8 2	7 6	7 3	7 0	8 1	7 6	7 2	7 0	7 9	7 5	7 2	6 9	7 7	7 4	7 1	6 9	6 8		
				1 . 2 5	8 5	8 0	7 7	7 4	8 4	8 0	7 7	7 4	8 2	7 9	7 6	7 4	8 1	7 8	7 5	7 3	7 2		
下方投影面積		c m ²		1 . 5	8 7	8 3	8 0	7 8	8 6	8 3	8 0	7 7	8 4	8 1	7 9	7 7	8 3	8 0	7 8	7 6	7 5		
		c m ²		2 . 0	9 0	8 7	8 4	8 2	8 9	8 6	8 4	8 1	8 7	8 5	8 3	8 1	8 5	8 3	8 2	8 0	7 8		
取付	器具間隔最大限			2 . 5	9 2	8 9	8 7	8 5	9 1	8 8	8 6	8 4	8 9	8 7	8 5	8 3	8 7	8 5	8 4	8 2	8 1		
高さ	横方向 (A)		縦方向 (B)	3 . 0	9 3	9 0	8 8	8 7	9 2	9 0	8 8	8 6	9 0	8 8	8 6	8 5	8 8	8 7	8 5	8 4	8 2		
H m	0 . 7 5 H m		0 . 7 5 H m	4 . 0	9 4	9 2	9 1	8 9	9 3	9 1	9 0	8 9	9 1	9 0	8 9	8 7	8 9	8 8	8 7	8 6	8 4		
				5 . 0	9 5	9 3	9 2	9 1	9 4	9 3	9 1	9 0	9 2	9 1	9 0	8 9	9 0	8 9	8 8	8 8	8 5		
				7 . 0	9 6	9 5	9 4	9 3	9 5	9 4	9 3	9 2	9 3	9 2	9 1	9 1	9 1	9 0	9 0	8 9	8 7		
				1 0 . 0	9 7	9 6	9 5	9 4	9 5	9 5	9 4	9 4	9 3	9 3	9 2	9 2	9 2	9 1	9 1	9 0	8 8		

