

屋内照明器具特性	
品番 (品名)	XSZR1060V
光源	LLD2410VCB1 ×1 500.0 lm
管理番号	K0192052 (0) DB 1
BZ分類	BZ1

器具効率		91 %	反 射 率	天井	80 %				70 %				50 %				30 %				0 %			
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %			
				床	10 %				10 %				10 %				10 %				0 %			
上方光束		0 %	室指数	照明率 (X0.01)																		Z	C	M
下方光束		91 %																						
保守率		良	0.63	0.6	71	64	60	57	70	63	59	57	68	63	59	56	67	62	59	56	55			
		中	0.6	0.8	77	72	67	65	77	71	67	64	75	70	67	64	74	69	66	64	63			
		否	0.56	1.0	82	76	73	70	81	76	72	70	79	75	72	69	77	74	71	69	68			
				1.25	85	80	77	74	84	80	77	74	82	79	76	74	81	78	75	73	72			
下方投影面積		c m ²		1.5	87	83	80	78	86	83	80	77	84	81	79	77	83	80	78	76	75			
等価発光面積		c m ²		2.0	90	87	84	82	89	86	84	81	87	85	83	81	85	83	82	80	78			
取付 高さ	器具間隔最大限			2.5	92	89	87	85	91	88	86	84	89	87	85	83	87	85	84	82	81			
	横方向 (A)		縦方向 (B)	3.0	93	90	88	87	92	90	88	86	90	88	86	85	88	87	85	84	82			
H m	0.75 H m		0.75 H m	4.0	94	92	91	89	93	91	90	89	91	90	89	87	89	88	87	86	84			
				5.0	95	93	92	91	94	93	91	90	92	91	90	89	90	89	88	88	85			
				7.0	96	95	94	93	95	94	93	92	93	92	91	91	91	90	90	89	87			
				10.0	97	96	95	94	95	95	94	94	93	93	92	92	92	91	91	90	88			

