

屋内照明器具特性	
品番 (品名)	XY2878
光源	LDT6L-G-E17/S/T6 ×1 810.0 lm
管理番号	K0179207(0)D 1
BZ分類	BZ5

器具効率		100 %		反射率	天井	80 %					70 %					50 %					30 %					0 %
					壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
					床	10 %					10 %					10 %					10 %					0 %
					室指数	照明率 (X0.01)																				ZCM
保守率		良 中 否	0.69	0.6	55	42	34	29	53	42	34	29	50	40	33	28	47	38	32	28	25					
			0.67	0.8	64	53	45	39	63	52	44	38	59	50	43	38	56	48	42	37	34					
			0.63	1.0	71	60	52	46	69	59	51	45	65	56	50	45	62	54	48	44	41					
				1.25	77	67	59	53	75	65	58	53	71	63	56	51	67	60	55	50	47					
下方投影面積		cm ²		1.5	81	72	64	59	79	70	63	58	75	67	61	57	71	65	60	55	52					
			等価発光面積	cm ²	2.0	87	79	72	67	84	77	71	66	80	74	69	64	76	71	67	63	59				
取付 高さ	器具間隔最大限			2.5	90	83	77	73	88	82	76	72	84	78	74	70	80	75	71	68	64					
	横方向 (A)		縦方向 (B)	3.0	93	87	81	77	90	85	80	76	86	82	77	74	82	78	75	72	68					
H m	1.29 H m		1.24 H m	4.0	96	91	87	83	94	89	85	82	90	86	82	79	86	83	80	77	73					
				5.0	98	94	90	87	96	92	89	85	92	89	86	83	88	85	83	81	76					
				7.0	100	97	94	92	98	95	93	90	94	92	90	87	90	88	87	85	80					
				10.0	102	100	98	96	100	98	96	94	96	94	93	91	93	91	90	88	84					

