

屋内照明器具特性	
品番 (品名)	XNW1 0 3 1 WW
光源	LED4000_85_785 ×1 785.0 lm
管理番号	K0167851 (0) DB 1
BZ分類	BZ1

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %		
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %		
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %		
上方光束		0 %	1 0 0 %	室指数	照明率 (X 0 . 0 1) Z C M																		
下方光束																							
保守率		良 中 否	0 . 8 3	0 . 6	7 4	6 6	6 1	5 7	7 3	6 6	6 1	5 7	7 2	6 5	6 0	5 7	7 0	6 4	6 0	5 7	5 5		
			0 . 8 1	0 . 8	8 3	7 5	7 0	6 7	8 2	7 5	7 0	6 7	8 0	7 4	7 0	6 6	7 8	7 3	6 9	6 6	6 5		
			0 . 7 7	1 . 0	8 8	8 1	7 7	7 3	8 7	8 1	7 6	7 3	8 5	8 0	7 6	7 3	8 3	7 9	7 5	7 2	7 1		
				1 . 2 5	9 2	8 6	8 2	7 9	9 1	8 6	8 2	7 9	8 9	8 4	8 1	7 8	8 7	8 3	8 0	7 8	7 6		
下方投影面積		c m ²	1 . 5	9 5	9 0	8 6	8 3	9 4	8 9	8 5	8 2	9 1	8 8	8 4	8 2	9 0	8 6	8 3	8 1	7 9			
等価発光面積			c m ²	2 . 0	9 8	9 4	9 1	8 8	9 7	9 3	9 0	8 8	9 5	9 2	8 9	8 7	9 3	9 0	8 8	8 6	8 4		
取付高さ	器具間隔最大限			2 . 5	1 0 0	9 7	9 4	9 2	9 9	9 6	9 3	9 1	9 7	9 4	9 2	9 0	9 5	9 3	9 1	8 9	8 7		
		横方向 (A)		縦方向 (B)		3 . 0	1 0 2	9 9	9 6	9 4	1 0 0	9 8	9 5	9 3	9 8	9 6	9 4	9 2	9 6	9 4	9 3	9 1	8 9
H m	1 . 0 7 H m	1 . 0 7 H m	4 . 0	1 0 3	1 0 1	9 9	9 7	1 0 2	1 0 0	9 8	9 7	1 0 0	9 8	9 7	9 5	9 8	9 6	9 5	9 4	9 2			
			5 . 0	1 0 4	1 0 2	1 0 1	9 9	1 0 3	1 0 1	1 0 0	9 9	1 0 1	1 0 0	9 8	9 7	9 9	9 8	9 7	9 6	9 3			
			7 . 0	1 0 5	1 0 4	1 0 3	1 0 2	1 0 4	1 0 3	1 0 2	1 0 1	1 0 2	1 0 1	1 0 0	9 9	1 0 0	9 9	9 8	9 8	9 5			
			1 0 . 0	1 0 6	1 0 5	1 0 4	1 0 4	1 0 5	1 0 4	1 0 3	1 0 3	1 0 3	1 0 2	1 0 1	1 0 1	1 0 1	1 0 0	1 0 0	9 9	9 6			

