

屋内照明器具特性	
品番 (品名)	YYY2 1 2 6 3 K
光源	LED3000_70_1320 ×1 1320.0 lm
管理番号	K0178713 (1) DR 1
B Z 分類	BZ5

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %			
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %			
				床	10 %				10 %				10 %				10 %				0 %			
上方光束		9 %	室指数	照明率 (X0.01)																		Z	C	M
下方光束		91 %																						
保守率		良 中 否	0.69	0.6	54	41	33	28	52	40	33	27	49	38	32	27	46	37	31	26	24			
			0.67	0.8	63	51	43	37	61	50	43	37	57	48	41	36	54	46	40	35	32			
			0.63	1.0	70	59	51	44	68	57	50	44	63	54	48	43	59	52	46	42	38			
				1.25	76	65	58	52	73	64	57	51	69	61	55	50	65	58	53	48	45			
下方投影面積		cm ²	1.5	80	70	63	57	77	69	62	56	73	65	60	55	69	62	57	53	49				
			2.0	85	77	71	65	83	76	69	64	78	72	67	62	74	69	64	60	56				
等価発光面積		cm ²	2.5	89	82	76	71	87	80	75	70	82	76	72	68	77	73	69	66	61				
			3.0	92	85	80	75	89	83	79	74	84	80	75	72	80	76	73	69	65				
1.5m		2.01 m	2.18 m	4.0	95	90	85	81	92	88	84	80	88	84	80	77	83	80	77	75	70			
2		2.65	2.75	5.0	97	93	89	85	95	91	87	84	90	87	84	81	85	83	80	78	73			
2.5		3.31	3.36	7.0	99	96	93	90	97	94	91	89	92	90	88	85	88	86	84	82	77			
3		3.95	3.97	10.0	101	99	97	94	99	97	95	93	94	93	91	89	90	89	87	86	81			

