

屋内照明器具特性	
品番 (品名)	X N W9 0 6 0 W N
光源	L E D 5 0 0 0 _ 8 0 _ 8 8 4 5 x 1 8 8 4 5 . 0 l m
管理番号	K 0 1 7 2 5 3 4 (0) D B 1
B Z 分類	B Z 1

器具効率		1 0 0 %	反 射 率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %						
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %						
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %						
上方光束		0 %	室指数	照明率 (X 0 . 0 1)																				Z C M			
下方光束		1 0 0 %																									
保守率		良 中 否	0 . 6	7 6	6 8	6 3	6 0	7 5	6 8	6 3	6 0	7 3	6 7	6 3	6 0	7 2	6 6	6 2	5 9	5 8							
			0 . 7 2	8 4	7 7	7 2	6 9	8 3	7 7	7 2	6 9	8 1	7 6	7 2	6 9	8 0	7 5	7 1	6 8	6 7							
			1 . 0	8 9	8 3	7 8	7 5	8 8	8 2	7 8	7 5	8 6	8 1	7 7	7 5	8 4	8 0	7 7	7 4	7 3							
			0 . 6 4	1 . 2 5	9 3	8 8	8 4	8 0	9 2	8 7	8 3	8 0	9 0	8 6	8 2	8 0	8 8	8 4	8 2	7 9	7 8						
下方投影面積		c m ²	1 . 5	9 5	9 1	8 7	8 4	9 4	9 0	8 7	8 4	9 2	8 9	8 6	8 3	9 0	8 7	8 5	8 2	8 1							
			2 . 0	9 9	9 5	9 2	8 9	9 8	9 4	9 1	8 9	9 5	9 2	9 0	8 8	9 3	9 1	8 9	8 7	8 5							
取付 高さ	器具間隔最大限		2 . 5	1 0 1	9 7	9 5	9 2	9 9	9 7	9 4	9 2	9 7	9 5	9 3	9 1	9 5	9 3	9 1	9 0	8 8							
	横方向 (A)	縦方向 (B)	3 . 0	1 0 2	9 9	9 7	9 5	1 0 1	9 8	9 6	9 4	9 9	9 6	9 5	9 3	9 7	9 5	9 3	9 2	9 0							
H m	0 . 7 9 H m	0 . 7 9 H m	4 . 0	1 0 4	1 0 1	9 9	9 8	1 0 2	1 0 0	9 9	9 7	1 0 0	9 9	9 7	9 6	9 8	9 7	9 5	9 4	9 2							
			5 . 0	1 0 4	1 0 3	1 0 1	1 0 0	1 0 3	1 0 2	1 0 0	9 9	1 0 1	1 0 0	9 9	9 7	9 9	9 8	9 7	9 6	9 4							
			7 . 0	1 0 6	1 0 4	1 0 3	1 0 2	1 0 4	1 0 3	1 0 2	1 0 1	1 0 2	1 0 1	1 0 0	9 9	1 0 0	9 9	9 8	9 8	9 5							
			1 0 . 0	1 0 6	1 0 5	1 0 5	1 0 4	1 0 5	1 0 4	1 0 3	1 0 3	1 0 3	1 0 2	1 0 2	1 0 1	1 0 1	1 0 0	1 0 0	9 9	9 6							

