

屋内照明器具特性	
品番 (品名)	XS Z B 1 5 0 2 A
光源	LLD2000CU1 ×1 566.0 lm
管理番号	K0199085 (0) DB 1
B Z 分類	BZ5

器具効率		71 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) ZCM																
保守率		良 中 否	0.63	0.6	41	32	26	22	40	31	26	22	38	31	26	22	36	30	25	22	21
			0.6	0.8	48	40	34	30	47	39	34	30	45	38	33	30	43	37	33	29	28
				1.0	52	45	39	35	51	44	39	35	49	43	38	35	47	42	38	35	33
			0.56	1.25	57	50	45	41	56	49	44	40	53	48	44	40	51	47	43	40	38
下方投影面積		cm ²		1.5	60	53	49	45	59	53	48	44	56	51	47	44	54	50	47	44	42
				2.0	64	58	54	51	63	58	54	50	60	56	53	50	58	55	52	49	47
等価発光面積		cm ²		2.5	66	62	58	55	65	61	57	54	63	59	56	54	61	58	55	53	51
				3.0	68	64	61	58	67	63	60	57	65	62	59	57	63	60	58	56	54
H m	1.25 H m	1.25 H m		4.0	70	67	64	62	69	66	64	61	67	65	62	60	65	63	61	60	58
				5.0	72	69	67	65	70	68	66	64	69	67	65	63	67	65	63	62	60
				7.0	73	71	69	68	72	70	69	67	70	69	67	66	68	67	66	65	63
				10.0	74	73	72	70	73	72	71	70	71	70	69	68	70	69	68	67	65

