

| 屋内照明器具特性 |                        |
|----------|------------------------|
| 品番 (品名)  | XS Z B 1 5 1 3 B       |
| 光源       | LLD2000CU1 x1 566.0 lm |
| 管理番号     | K0199085 ( 0 ) DB 1    |
| B Z 分類   | BZ5                    |

| 器具効率           |                     | 71 %                | 反射率  | 天井   | 80 %              |    |    |    | 70 % |    |    |    | 50 % |    |    |    | 30 % |    |    |    | 0 % |
|----------------|---------------------|---------------------|------|------|-------------------|----|----|----|------|----|----|----|------|----|----|----|------|----|----|----|-----|
|                |                     |                     |      | 壁    | 70                | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 0 % |
|                |                     |                     |      | 床    | 10 %              |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 0 % |
|                |                     |                     |      | 室指数  | 照明率 ( X0.01 ) ZCM |    |    |    |      |    |    |    |      |    |    |    |      |    |    |    |     |
| 保守率            |                     | 良<br>中<br>否         | 0.63 | 0.6  | 41                | 32 | 26 | 22 | 40   | 31 | 26 | 22 | 38   | 31 | 26 | 22 | 36   | 30 | 25 | 22 | 21  |
|                |                     |                     | 0.6  | 0.8  | 48                | 40 | 34 | 30 | 47   | 39 | 34 | 30 | 45   | 38 | 33 | 30 | 43   | 37 | 33 | 29 | 28  |
|                |                     |                     |      | 1.0  | 52                | 45 | 39 | 35 | 51   | 44 | 39 | 35 | 49   | 43 | 38 | 35 | 47   | 42 | 38 | 35 | 33  |
|                |                     |                     | 0.56 | 1.25 | 57                | 50 | 45 | 41 | 56   | 49 | 44 | 40 | 53   | 48 | 44 | 40 | 51   | 47 | 43 | 40 | 38  |
| 下方投影面積         |                     | cm <sup>2</sup>     |      | 1.5  | 60                | 53 | 49 | 45 | 59   | 53 | 48 | 44 | 56   | 51 | 47 | 44 | 54   | 50 | 47 | 44 | 42  |
|                |                     |                     |      | 2.0  | 64                | 58 | 54 | 51 | 63   | 58 | 54 | 50 | 60   | 56 | 53 | 50 | 58   | 55 | 52 | 49 | 47  |
| 等価発光面積         |                     | cm <sup>2</sup>     |      | 2.5  | 66                | 62 | 58 | 55 | 65   | 61 | 57 | 54 | 63   | 59 | 56 | 54 | 61   | 58 | 55 | 53 | 51  |
|                |                     |                     |      | 3.0  | 68                | 64 | 61 | 58 | 67   | 63 | 60 | 57 | 65   | 62 | 59 | 57 | 63   | 60 | 58 | 56 | 54  |
| H <sub>m</sub> | 1.25 H <sub>m</sub> | 1.25 H <sub>m</sub> |      | 4.0  | 70                | 67 | 64 | 62 | 69   | 66 | 64 | 61 | 67   | 65 | 62 | 60 | 65   | 63 | 61 | 60 | 58  |
|                |                     |                     |      | 5.0  | 72                | 69 | 67 | 65 | 70   | 68 | 66 | 64 | 69   | 67 | 65 | 63 | 67   | 65 | 63 | 62 | 60  |
|                |                     |                     |      | 7.0  | 73                | 71 | 69 | 68 | 72   | 70 | 69 | 67 | 70   | 69 | 67 | 66 | 68   | 67 | 66 | 65 | 63  |
|                |                     |                     |      | 10.0 | 74                | 73 | 72 | 70 | 73   | 72 | 71 | 70 | 71   | 70 | 69 | 68 | 70   | 69 | 68 | 67 | 65  |

