

屋内照明器具特性	
品番 (品名)	XS Z B 1 5 2 2 W
光源	LLD2000LCB1 ×1 531.0 lm
管理番号	K0199981 (0) DR 1
B Z 分類	BZ5

器具効率		67 %	反射率	天井	80 %				70 %				50 %				30 %				0 %		
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %		
				床	10 %				10 %				10 %				10 %				0 %		
上方光束		0 %	室指数	照明率 (X0.01)																		Z	CM
下方光束		67 %																					
保守率		良 中 否	0.63	0.6	38	30	25	21	37	30	25	21	36	29	24	21	34	28	24	21	20		
			0.6	0.8	45	37	32	28	44	37	32	28	42	36	31	28	40	35	31	28	26		
			0.56	1.0	49	42	37	33	48	42	37	33	46	41	36	33	44	39	36	33	31		
				1.25	53	47	42	38	52	46	42	38	50	45	41	38	48	44	40	37	36		
下方投影面積		cm ²	1.5	56	50	46	42	55	50	45	42	53	48	44	41	51	47	44	41	39			
等価発光面積		cm ²	2.0	60	55	51	48	59	54	50	47	57	53	50	47	55	52	49	46	45			
取付 高さ	器具間隔最大限		2.5	62	58	54	51	61	57	54	51	59	56	53	50	57	54	52	50	48			
	横方向 (A)	縦方向 (B)	3.0	64	60	57	54	63	59	56	54	61	58	55	53	59	57	54	52	51			
H m	1.25 H m	1.25 H m	4.0	66	63	60	58	65	62	60	58	63	61	59	57	61	59	58	56	54			
			5.0	67	65	63	61	66	64	62	60	64	63	61	59	63	61	60	58	56			
			7.0	69	67	65	64	68	66	65	63	66	65	63	62	64	63	62	61	59			
			10.0	70	69	67	66	69	68	67	66	67	66	65	64	66	65	64	63	61			

