

屋内照明器具特性	
品番 (品名)	X S Z B 7 1 0 3 B
光源	L L D 2 0 0 0 L C B 1 × 1 5 3 1 . 0 l m
管理番号	K 0 1 9 9 9 8 1 (0) D R 1
B Z 分類	B Z 5

器具効率		6 7 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
上方光束		0 %	室指数	照明率 (X 0 . 0 1)																		Z C M
下方光束		6 7 %																				
保守率		良 中 否	0 . 6 3	0 . 6	3 8	3 0	2 5	2 1	3 7	3 0	2 5	2 1	3 6	2 9	2 4	2 1	3 4	2 8	2 4	2 1	2 0	
			0 . 6	0 . 8	4 5	3 7	3 2	2 8	4 4	3 7	3 2	2 8	4 2	3 6	3 1	2 8	4 0	3 5	3 1	2 8	2 6	
			0 . 5 6	1 . 0	4 9	4 2	3 7	3 3	4 8	4 2	3 7	3 3	4 6	4 1	3 6	3 3	4 4	3 9	3 6	3 3	3 1	
				1 . 2 5	5 3	4 7	4 2	3 8	5 2	4 6	4 2	3 8	5 0	4 5	4 1	3 8	4 8	4 4	4 0	3 7	3 6	
下方投影面積		c m ²	1 . 5	5 6	5 0	4 6	4 2	5 5	5 0	4 5	4 2	5 3	4 8	4 4	4 1	5 1	4 7	4 4	4 1	3 9		
等価発光面積			c m ²	2 . 0	6 0	5 5	5 1	4 8	5 9	5 4	5 0	4 7	5 7	5 3	5 0	4 7	5 5	5 2	4 9	4 6	4 5	
取付高さ	器具間隔最大限		2 . 5	6 2	5 8	5 4	5 1	6 1	5 7	5 4	5 1	5 9	5 6	5 3	5 0	5 7	5 4	5 2	5 0	4 8		
	横方向 (A)		縦方向 (B)	3 . 0	6 4	6 0	5 7	5 4	6 3	5 9	5 6	5 4	6 1	5 8	5 5	5 3	5 9	5 7	5 4	5 2	5 1	
H m	1 . 2 5 H m	1 . 2 5 H m	4 . 0	6 6	6 3	6 0	5 8	6 5	6 2	6 0	5 8	6 3	6 1	5 9	5 7	6 1	5 9	5 8	5 6	5 4		
			5 . 0	6 7	6 5	6 3	6 1	6 6	6 4	6 2	6 0	6 4	6 3	6 1	5 9	6 3	6 1	6 0	5 8	5 6		
			7 . 0	6 9	6 7	6 5	6 4	6 8	6 6	6 5	6 3	6 6	6 5	6 3	6 2	6 4	6 3	6 2	6 1	5 9		
			1 0 . 0	7 0	6 9	6 7	6 6	6 9	6 8	6 7	6 6	6 7	6 6	6 5	6 4	6 6	6 5	6 4	6 3	6 1		

