

屋内照明器具特性	
品番 (品名)	XYM2 0 3 3
光源	LED5000_85_32000 ×1 32000.0 lm
管理番号	K0160688 (0) DR 1
B Z 分類	BZ5

器具効率		100 %		反射率	天井	80 %				70 %				50 %				30 %				0 %
					壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
					床	10 %				10 %				10 %				10 %				0 %
					室指数	照明率 (X0.01) Z CM																
保守率		良 中 否	0.83	0.6	56	44	36	30	55	43	36	30	52	42	35	30	50	41	34	30	28	
			0.81	0.8	66	55	47	41	65	54	46	41	62	52	46	40	59	51	45	40	38	
			0.77	1.0	73	62	54	49	71	61	54	48	68	59	53	48	65	58	52	47	45	
				1.25	79	69	62	56	77	68	61	56	74	66	60	55	71	64	59	55	52	
下方投影面積		cm ²		1.5	83	74	67	62	81	73	67	61	78	71	65	61	75	69	64	60	57	
			等価発光面積		cm ²	2.0	89	81	75	70	87	80	74	70	84	78	73	69	80	76	71	68
取付	器具間隔最大限			2.5	92	86	81	76	91	85	80	75	87	82	78	74	84	80	76	73	70	
高さ	横方向 (A)		縦方向 (B)	3.0	95	89	84	80	93	88	83	80	90	85	82	78	87	83	80	77	74	
H m	1.31 H m		1.31 H m	4.0	98	93	90	86	96	92	89	85	93	90	86	84	90	87	85	82	79	
				5.0	100	96	93	90	98	95	92	89	95	92	90	87	92	90	88	85	82	
				7.0	102	99	97	94	100	98	96	93	97	95	93	91	95	93	91	90	86	
				10.0	104	102	100	98	102	100	99	97	99	98	96	95	97	95	94	93	89	

