

屋内照明器具特性	
品番 (品名)	XYM2 0 4 2
光源	LED5000_85_21000 ×1 21000.0 lm
管理番号	K0160686 (0) DR 1
BZ分類	BZ5 / 0.7 / BZ4

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %					
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %					
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %					
上方光束		0 %	室指数	照明率 (X 0 . 0 1)																			Z C M			
下方光束				1 0 0 %																						
保守率		良 中 否	0 . 8 3	0 . 6	5 8	4 6	3 9	3 4	5 7	4 6	3 9	3 3	5 5	4 5	3 8	3 3	5 3	4 4	3 8	3 3	3 1					
			0 . 8 1	0 . 8	6 9	5 8	5 0	4 5	6 7	5 7	5 0	4 5	6 5	5 6	4 9	4 5	6 2	5 5	4 9	4 4	4 2					
			0 . 7 7	1 . 0	7 6	6 6	5 8	5 3	7 4	6 5	5 8	5 3	7 1	6 3	5 7	5 3	6 9	6 2	5 6	5 2	5 0					
				1 . 2 5	8 2	7 3	6 6	6 1	8 0	7 2	6 6	6 1	7 7	7 0	6 5	6 0	7 5	6 9	6 4	6 0	5 8					
下方投影面積		c m ²	1 . 5	8 6	7 8	7 2	6 7	8 4	7 7	7 1	6 6	8 2	7 5	7 0	6 6	7 9	7 3	6 9	6 5	6 3						
等価発光面積			c m ²	2 . 0	9 1	8 5	7 9	7 5	9 0	8 4	7 9	7 5	8 7	8 2	7 8	7 4	8 4	8 0	7 6	7 3	7 1					
取付高さ	器具間隔最大限			2 . 5	9 5	8 9	8 5	8 1	9 3	8 8	8 4	8 0	9 0	8 6	8 2	7 9	8 8	8 4	8 1	7 8	7 6					
横方向 (A)		縦方向 (B)		3 . 0	9 7	9 2	8 8	8 5	9 6	9 1	8 7	8 4	9 3	8 9	8 6	8 3	9 0	8 7	8 4	8 2	7 9					
H m	1 . 3 1 H m	1 . 3 0 H m	4 . 0	1 0 0	9 6	9 3	9 0	9 9	9 5	9 2	8 9	9 6	9 3	9 0	8 8	9 3	9 1	8 9	8 7	8 4						
			5 . 0	1 0 2	9 9	9 6	9 3	1 0 0	9 7	9 5	9 2	9 8	9 5	9 3	9 1	9 5	9 3	9 1	9 0	8 7						
			7 . 0	1 0 4	1 0 1	9 9	9 7	1 0 2	1 0 0	9 8	9 6	1 0 0	9 8	9 6	9 5	9 7	9 6	9 4	9 3	9 0						
			1 0 . 0	1 0 5	1 0 3	1 0 2	1 0 0	1 0 4	1 0 2	1 0 1	9 9	1 0 1	1 0 0	9 9	9 8	9 9	9 8	9 7	9 6	9 3						

