

屋内照明器具特性	
品番 (品名)	XSZP3565V+LGK9100W
光源	LLD3410VCB1 ×1 700.0 l m
管理番号	K0191396 (0) DB 1
BZ分類	BZ1

器具効率		97 %	反射率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
				床	10 %				10 %				10 %				10 %				0 %	
上方光束		0 %	室指数	照明率 (X0.01)																		Z C M
下方光束		97 %																				
保守率		良	0.67	0.6	88	84	81	79	87	83	81	79	86	83	80	79	85	82	80	79	78	
		中	0.63	0.8	92	88	86	84	91	88	85	83	90	87	85	83	89	86	84	83	82	
		否	0.56	1.0	95	91	89	87	94	91	88	87	92	90	88	86	91	89	87	86	85	
		0.56	1.25	97	94	91	90	96	93	91	89	94	92	90	89	93	91	90	88	87		
下方投影面積		c m ²	1.5	98	95	93	91	97	95	93	91	96	93	92	90	94	92	91	90	89		
			2.0	100	97	96	94	99	97	95	94	97	95	94	93	95	94	93	92	90		
取付高さ	器具間隔最大限		2.5	101	99	97	96	100	98	97	95	98	97	95	94	96	95	94	93	92		
	横方向 (A)	縦方向 (B)	3.0	101	100	98	97	100	99	98	97	99	97	96	95	97	96	95	94	92		
H m	0.79 H m	0.79 H m	4.0	102	101	100	99	101	100	99	98	99	98	98	97	97	97	96	95	93		
			5.0	103	102	101	100	102	101	100	99	100	99	98	98	98	97	97	96	94		
			7.0	103	102	102	101	102	101	100	100	100	99	99	98	98	97	97	96	95		
			10.0	104	103	103	102	103	102	101	101	101	100	99	99	98	98	98	98	95		

