

屋内照明器具特性	
品番 (品名)	XS Z B 1 5 1 3 B
光源	LLD2000CU1 x1 566.0 lm
管理番号	K0199085 (0) DB 1
BZ分類	BZ5

器具効率		71 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) ZCM																
保守率		良 中 否	0.63	0.6	41	32	26	22	40	31	26	22	38	31	26	22	36	30	25	22	21
			0.6	0.8	48	40	34	30	47	39	34	30	45	38	33	30	43	37	33	29	28
			0.56	1.0	52	45	39	35	51	44	39	35	49	43	38	35	47	42	38	35	33
				1.25	57	50	45	41	56	49	44	40	53	48	44	40	51	47	43	40	38
下方投影面積 等価発光面積		cm ²		1.5	60	53	49	45	59	53	48	44	56	51	47	44	54	50	47	44	42
				2.0	64	58	54	51	63	58	54	50	60	56	53	50	58	55	52	49	47
				2.5	66	62	58	55	65	61	57	54	63	59	56	54	61	58	55	53	51
取付 高さ	器具間隔最大限			3.0	68	64	61	58	67	63	60	57	65	62	59	57	63	60	58	56	54
	横方向 (A)	縦方向 (B)		4.0	70	67	64	62	69	66	64	61	67	65	62	60	65	63	61	60	58
H _m	1.25H _m	1.25H _m		5.0	72	69	67	65	70	68	66	64	69	67	65	63	67	65	63	62	60
				7.0	73	71	69	68	72	70	69	67	70	69	67	66	68	67	66	65	63
				10.0	74	73	72	70	73	72	71	70	71	70	69	68	70	69	68	67	65

