

| 屋内照明器具特性 |                         |
|----------|-------------------------|
| 品番 (品名)  | YYY41000                |
| 光源       | LLD4000LCB1 ×2 845.0 lm |
| 管理番号     | K0194490 (1) D 1        |
| BZ分類     | BZ1                     |

| 器具効率           |                    | 14 %               | 反射率     | 天井   | 80 %              |    |    |    | 70 % |    |    |    | 50 % |    |    |    | 30 % |    |    |    | 0 % |
|----------------|--------------------|--------------------|---------|------|-------------------|----|----|----|------|----|----|----|------|----|----|----|------|----|----|----|-----|
|                |                    |                    |         | 壁    | 70                | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 0 % |
|                |                    |                    |         | 床    | 10 %              |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 0 % |
|                |                    |                    |         | 室指数  | 照明率 ( X0.01 ) ZCM |    |    |    |      |    |    |    |      |    |    |    |      |    |    |    |     |
| 保守率            |                    | 良<br>中<br>否        | 0.63    | 0.6  | 9                 | 7  | 7  | 6  | 8    | 7  | 6  | 6  | 7    | 6  | 6  | 5  | 6    | 6  | 5  | 5  | 4   |
|                |                    |                    | 0.6     | 0.8  | 10                | 8  | 8  | 7  | 9    | 8  | 7  | 7  | 8    | 7  | 7  | 6  | 7    | 6  | 6  | 6  | 5   |
|                |                    |                    | 0.56    | 1.0  | 10                | 9  | 9  | 8  | 10   | 9  | 8  | 8  | 8    | 8  | 7  | 7  | 7    | 7  | 7  | 6  | 5   |
|                |                    |                    |         | 1.25 | 11                | 10 | 9  | 9  | 10   | 9  | 9  | 8  | 9    | 8  | 8  | 8  | 8    | 7  | 7  | 7  | 6   |
| 下方投影面積         |                    | cm <sup>2</sup>    | 1.5     | 11   | 10                | 10 | 9  | 11 | 10   | 9  | 9  | 9  | 9    | 8  | 8  | 8  | 8    | 7  | 7  | 6  |     |
| 等価発光面積         |                    |                    | 2.0     | 12   | 11                | 11 | 10 | 11 | 10   | 10 | 10 | 10 | 9    | 9  | 9  | 8  | 8    | 8  | 8  | 6  |     |
| 取付高さ           | 器具間隔最大限            |                    |         | 2.5  | 12                | 12 | 11 | 11 | 11   | 11 | 10 | 10 | 10   | 9  | 9  | 9  | 8    | 8  | 8  | 8  | 6   |
|                | 横方向 (A)            |                    | 縦方向 (B) | 3.0  | 12                | 12 | 11 | 11 | 12   | 11 | 11 | 10 | 10   | 10 | 9  | 9  | 9    | 8  | 8  | 8  | 6   |
| H <sub>m</sub> | 0.71H <sub>m</sub> | 0.72H <sub>m</sub> | 4.0     | 13   | 12                | 12 | 12 | 12 | 11   | 11 | 11 | 10 | 10   | 10 | 10 | 9  | 9    | 8  | 8  | 6  |     |
|                |                    |                    | 5.0     | 13   | 12                | 12 | 12 | 12 | 12   | 11 | 11 | 10 | 10   | 10 | 10 | 9  | 9    | 9  | 8  | 7  |     |
|                |                    |                    | 7.0     | 13   | 13                | 12 | 12 | 12 | 12   | 12 | 12 | 10 | 10   | 10 | 10 | 9  | 9    | 9  | 9  | 7  |     |
|                |                    |                    | 10.0    | 13   | 13                | 13 | 13 | 12 | 12   | 12 | 12 | 11 | 10   | 10 | 10 | 9  | 9    | 9  | 9  | 7  |     |

