

屋内照明器具特性	
品番 (品名)	YYY41000
光源	LLD40001CQ1 ×2 845.0 lm
管理番号	K0194446 (1) D 1
BZ分類	BZ1

器具効率		15 % 上方光束 8 % 下方光束	反射率	天井	80 %					70 %					50 %					30 %					0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %					10 %					10 %					10 %					0 %
				室指数	照明率 (X0.01) ZCM																				
保守率		良 中 否	0.63	0.6	0.56	0.6	9	8	7	6	8	7	7	6	7	7	6	6	7	6	6	5	5		
			0.6	0.8	1.0	9	8	7	9	8	8	7	8	7	7	7	7	7	7	6	6	5			
			0.56	1.0	1.1	10	9	8	10	9	8	8	9	8	8	7	8	7	7	7	7	6			
			0.56	1.25	1.1	10	10	9	10	10	9	9	9	9	8	8	8	8	7	7	6				
下方投影面積		cm ²	1.5	1.2	1.1	10	10	11	10	10	9	9	9	9	8	8	8	8	8	8	7	6			
等価発光面積			2.0	1.2	1.1	11	10	11	11	10	10	10	9	9	9	8	8	8	8	8	6				
取付高さ	器具間隔最大限					2.5	1.3	1.2	1.1	1.1	1.2	1.1	1.1	1.0	1.0	1.0	9	9	9	8	8	8	6		
	横方向 (A)			縦方向 (B)		3.0	1.3	1.2	1.2	1.1	1.2	1.1	1.1	1.1	1.0	1.0	1.0	9	9	9	8	8	6		
H m	0.74 H m			0.74 H m		4.0	1.3	1.3	1.2	1.2	1.2	1.2	1.1	1.1	1.0	1.0	1.0	9	9	9	9	7			
						5.0	1.3	1.3	1.3	1.2	1.2	1.2	1.2	1.1	1.0	1.0	1.0	9	9	9	9	7			
						7.0	1.3	1.3	1.3	1.3	1.3	1.2	1.2	1.2	1.1	1.1	1.1	1.0	9	9	9	7			
						10.0	1.4	1.3	1.3	1.3	1.3	1.3	1.2	1.2	1.1	1.1	1.1	1.1	9	9	9	7			

