

屋内照明器具特性	
品番 (品名)	YYY41000
光源	LLD40402CQ1 (SHUKOU) ×2 620.0 l m
管理番号	K0194449 (1) D 1
BZ分類	BZ1

器具効率		58 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) ZCM																
保守率		良 中 否	0.63	0.6	38	33	30	28	36	32	29	27	32	29	27	26	28	26	25	24	22
			0.6	0.8	41	37	34	32	39	35	33	31	35	32	30	29	31	29	28	27	23
				1.0	44	40	37	35	41	38	36	34	37	34	33	31	32	31	29	29	24
			0.56	1.25	46	43	40	38	43	40	38	36	38	36	35	33	33	32	31	30	25
下方投影面積		cm ²		1.5	48	45	42	40	45	42	40	38	39	37	36	35	34	33	32	31	26
			等価発光面積	cm ²	2.0	50	47	45	43	47	44	43	41	41	39	38	37	35	34	33	33
取付 高さ	器具間隔最大限			2.5	51	49	47	45	48	46	44	43	42	40	39	38	36	35	34	34	27
	横方向 (A)		縦方向 (B)	3.0	52	50	48	47	49	47	46	44	42	41	40	39	36	36	35	34	27
H m	0.70 H m		0.69 H m	4.0	53	51	50	49	50	48	47	46	43	42	41	41	37	36	36	35	28
				5.0	54	52	51	50	50	49	48	47	43	43	42	42	37	37	36	36	28
				7.0	54	53	53	52	51	50	49	49	44	44	43	43	38	37	37	37	28
				10.0	55	54	54	53	51	51	50	50	44	44	44	43	38	38	37	37	28

