

屋内照明器具特性	
品番 (品名)	YYY41000
光源	LLD3000CU1 x2 795.0 lm
管理番号	K0194450 (1) D 1
BZ分類	BZ1

器具効率		16 % 上方光束 8 % 下方光束 8 %	反射率	天井	80 %				70 %				50 %				30 %				0 %		
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %		
				床	10 %				10 %				10 %				10 %				0 %		
				室指数	照明率 (X0.01) ZCM																		
保守率		良 中 否	0.63	0.6	0.56	0.6	9	8	7	6	9	7	7	6	8	7	6	6	7	6	6	5	5
			0.6	0.8	1.0	9	8	8	10	9	8	7	9	8	7	7	7	7	7	6	6	5	
			0.56	1.0	1.1	10	9	9	11	10	9	8	9	8	8	7	8	7	7	7	7	6	
			1.25	1.2	1.1	10	9	9	11	10	10	9	10	9	9	8	8	8	8	8	7	6	
下方投影面積		cm ²	1.5	1.2	1.1	11	10	12	11	10	10	10	9	9	9	9	8	8	8	8	6		
等価発光面積			2.0	1.3	1.2	12	11	12	11	11	10	10	10	10	9	9	9	8	8	6			
取付 高さ	器具間隔最大限				2.5	1.3	1.3	1.2	1.2	1.2	1.2	1.1	1.1	1.1	1.0	1.0	1.0	9	9	9	8	7	
	横方向 (A)		縦方向 (B)		3.0	1.4	1.3	1.3	1.2	1.3	1.2	1.2	1.1	1.1	1.1	1.0	1.0	9	9	9	9	7	
H m	0.75 H m		0.74 H m		4.0	1.4	1.4	1.3	1.3	1.3	1.3	1.2	1.2	1.1	1.1	1.1	1.0	9	9	9	9	7	
					5.0	1.4	1.4	1.3	1.3	1.3	1.3	1.3	1.2	1.1	1.1	1.1	1.1	1.0	9	9	9	7	
					7.0	1.4	1.4	1.4	1.4	1.3	1.3	1.3	1.3	1.2	1.1	1.1	1.1	1.0	1.0	1.0	9	7	
					10.0	1.5	1.4	1.4	1.4	1.4	1.3	1.3	1.3	1.2	1.2	1.1	1.1	1.0	1.0	1.0	1.0	7	

